

屋内照明器具特性

品番 (品名)	XLGD670	
光源	LED2700_70_270 x1	270.0 lm
管理番号	K0162314(0)DB1	
BZ分類	BZ3/3.5/BZ4	

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	2%	床	10%				10%				10%				10%				0%	
下方光束	98%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	62	52	45	40	61	51	44	40	59	50	44	40	57	49	43	39	37
	中	0.63	0.8	72	62	56	51	71	62	55	51	68	60	54	50	66	59	54	50	48
	否	0.56	1.0	79	70	63	58	77	69	63	58	74	67	62	57	72	65	61	57	55
			1.25	84	76	70	65	82	75	69	65	79	73	68	64	77	71	67	63	61
下方投影面積	c m ²		1.5	88	80	75	70	86	79	74	70	83	77	72	69	80	75	71	68	65
	等価発光面積		c m ²	2.0	92	86	81	77	91	85	80	76	87	83	79	85	81	77	74	72
取付高さ	器具間隔最大限		2.5	95	90	86	82	93	89	85	81	90	86	83	80	88	84	81	79	76
	横方向 (A)	縦方向 (B)	3.0	97	93	89	85	95	91	88	84	92	89	86	83	90	87	84	82	79
H m	0.66 H m	0.87 H m	4.0	100	96	93	90	98	95	92	89	95	92	90	87	92	90	88	86	83
			5.0	101	98	95	93	100	97	94	92	97	94	92	90	94	92	90	88	85
			7.0	103	101	99	97	101	99	97	95	98	97	95	93	96	94	93	91	88
			10.0	104	103	101	99	103	101	100	98	100	99	97	96	97	96	95	94	91

