

屋内照明器具特性

品番 (品名)	XLGDC660K	
光源	LGWC71660K x1	435.0 lm
管理番号	K0125533(1)DB1	
BZ分類	BZ3/0.9/BZ2/4.5/BZ3/6.0/BZ2	

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
下方光束	100%	床		10%				10%				10%				10%				0%			
室指数			照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	64	54	47	43	63	53	47	42	61	52	47	42	59	51	46	42	40			
	中	0.63	0.8	75	66	59	55	74	65	59	55	72	64	59	54	69	63	58	54	52			
	否	0.56	1.0	82	73	68	63	80	73	67	63	78	71	66	63	76	70	66	62	60			
			1.25	87	80	74	70	86	79	74	70	83	78	73	69	81	76	72	69	67			
下方投影面積	cm ²		1.5	91	84	79	75	89	83	78	75	87	82	77	74	84	80	76	73	72			
	等価発光面積		2.0	95	90	85	82	94	89	85	81	91	87	84	81	89	85	82	80	78			
取付高さ	器具間隔最大限		2.5	98	93	89	86	96	92	89	86	94	90	87	85	91	89	86	84	82			
	横方向 (A)	縦方向 (B)	3.0	99	96	92	89	98	95	92	89	96	93	90	88	93	91	89	87	84			
Hm	1.27Hm	1.27Hm	4.0	102	99	96	94	100	98	95	93	98	96	94	92	96	94	92	90	88			
			5.0	103	101	98	96	102	99	97	96	99	97	96	94	97	95	94	93	90			
			7.0	104	103	101	99	103	102	100	99	101	99	98	97	99	97	96	95	93			
			10.0	106	104	103	102	104	103	102	101	102	101	100	99	100	99	98	97	95			

