

屋内照明器具特性

品番 (品名)	S Q 4 3 8	
光源	LED6200_70_1025 x1 1025.0 lm	
管理番号	K0157897 (0) DB 1	
BZ分類	BZ5/1.1/BZ4	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	100 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.69	0.6	57	45	37	32	56	44	37	32	53	43	36	32	51	42	36	31	29
		0.67	0.8	67	56	48	43	66	55	48	42	63	54	47	42	61	53	47	42	40
			1.0	74	64	56	50	73	63	56	50	70	61	55	50	67	60	54	50	47
		0.63	1.25	80	71	64	58	79	70	63	58	76	68	62	58	73	66	61	57	55
下方投影面積	c m ²	1.5	85	76	69	64	83	75	69	64	80	73	68	63	77	71	67	63	60	
		2.0	90	83	77	73	89	82	77	72	86	80	75	71	83	78	74	71	68	
取付高さ	器具間隔最大限		2.5	94	88	83	78	92	87	82	78	89	85	81	77	87	83	79	76	74
	横方向 (A)	縦方向 (B)	3.0	96	91	87	83	95	90	86	82	92	88	84	81	89	86	83	80	77
H m	1.27 H m	1.27 H m	4.0	99	95	92	88	98	94	91	88	95	92	89	87	92	90	87	85	83
			5.0	101	98	95	92	100	97	94	91	97	94	92	90	95	92	90	89	86
			7.0	103	101	99	96	102	100	98	96	99	97	96	94	97	95	94	92	90
			10.0	105	103	101	100	103	102	100	99	101	100	98	97	99	98	96	95	93

