

# 屋内照明器具特性

品番 (品名)	XLX400TEV									
光源	LED3500_85_9260 x1					9260.0 lm				
管理番号	K0129806(2)DB1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	2%	室指数	照明率 ( X0.01)																ZCM		
下方光束	98%																				
保守率	良 中 否	0.83	0.6	5.5	4.2	3.4	2.9	5.3	4.2	3.4	2.9	5.1	4.0	3.3	2.8	4.8	3.9	3.3	2.8	2.6	
		0.81	0.8	6.5	5.3	4.4	3.9	6.3	5.2	4.4	3.8	6.0	5.0	4.3	3.8	5.7	4.9	4.2	3.8	3.5	
		0.77	1.0	7.1	6.0	5.2	4.6	6.9	5.9	5.1	4.6	6.6	5.7	5.0	4.5	6.3	5.5	4.9	4.5	4.2	
			1.25	7.7	6.7	5.9	5.3	7.5	6.6	5.8	5.3	7.2	6.4	5.7	5.2	6.9	6.2	5.6	5.1	4.9	
下方投影面積	c m <sup>2</sup>	1.5	8.1	7.2	6.5	5.9	7.9	7.1	6.4	5.8	7.6	6.8	6.2	5.7	7.3	6.6	6.1	5.7	5.4		
		2.0	8.7	7.9	7.2	6.7	8.5	7.8	7.2	6.6	8.2	7.5	7.0	6.5	7.8	7.3	6.8	6.4	6.2		
取付高さ	器具間隔最大限		2.5	9.1	8.4	7.8	7.3	8.9	8.2	7.7	7.2	8.5	8.0	7.5	7.1	8.2	7.7	7.3	7.0	6.7	
	横方向 (A)	縦方向 (B)	3.0	9.3	8.7	8.2	7.7	9.1	8.6	8.1	7.6	8.8	8.3	7.9	7.5	8.5	8.1	7.7	7.4	7.1	
1.5m	2.02m	2.2m	4.0	9.7	9.2	8.7	8.3	9.5	9.0	8.6	8.2	9.1	8.8	8.4	8.1	8.8	8.5	8.2	7.9	7.6	
2	2.67	2.79	5.0	9.9	9.4	9.1	8.7	9.7	9.3	9.0	8.6	9.4	9.0	8.7	8.5	9.1	8.8	8.5	8.3	8.0	
2.5	3.32	3.39	7.0	10.1	9.8	9.5	9.2	9.9	9.6	9.4	9.1	9.6	9.4	9.1	8.9	9.3	9.1	8.9	8.7	8.4	
3	3.97	4.01	10.0	10.3	10.1	9.8	9.6	10.1	9.9	9.7	9.5	9.8	9.6	9.5	9.3	9.5	9.4	9.2	9.1	8.8	

