

屋内照明器具特性

品番 (品名)	XLX405GEV														
光源	LED3500_85_8530 x1 8530.0 lm														
管理番号	K0134370(3)DB1														
BZ分類	BZ4														

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	5%	床	10%				10%				10%				10%				0%	
下方光束	95%	室指数	照明率 (X0.01) ZCM																	
保守率	良 0.81 中 0.77 否 0.68	0.6	59	48	40	35	58	47	40	35	55	46	39	35	52	44	39	34	32	
		0.8	69	59	52	46	68	58	51	46	65	56	50	46	62	54	49	45	42	
		1.0	76	66	60	54	74	65	59	54	71	63	58	53	68	61	56	52	50	
		1.25	82	73	67	62	80	72	66	61	76	70	64	60	73	68	63	59	56	
下方投影面積	c m ²	1.5	86	78	72	67	84	77	71	67	80	74	69	65	77	72	68	64	61	
		2.0	91	85	79	75	89	83	78	74	85	80	76	73	82	78	74	71	68	
取付高さ	器具間隔最大限		2.5	94	89	84	80	92	87	83	79	88	84	81	78	85	82	79	76	73
	横方向 (A)	縦方向 (B)	3.0	96	92	88	84	94	90	86	83	91	87	84	81	87	84	82	79	76
1.5m	1.86m	2.2m	4.0	99	95	92	89	97	94	91	88	93	91	88	86	90	88	86	84	80
2	2.47	2.78	5.0	101	98	95	92	99	96	93	91	95	93	91	89	92	90	88	87	83
2.5	3.08	3.38	7.0	102	100	98	96	101	99	97	95	97	95	94	92	94	92	91	90	86
3	3.68	3.99	10.0	104	102	101	99	102	101	99	98	99	97	96	95	95	94	93	92	88

