

# 屋内照明器具特性

|         |                              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|------------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XLF213NTNK(JYOUJI_WALL)      |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_1500 x1 1500.0 lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0153253(2)DR1               |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ8/0.7/BZ7                  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                  |         |             |    |     |    |     |    |     |    |     |    |     |    |     |    |     |    |     |    |    |
|--------|------------------|---------|-------------|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|-----|----|----|
| 器具効率   | 100%             | 天井      | 80%         |    |     |    | 70% |    |     |    | 50% |    |     |    | 30% |    |     |    | 0%  |    |    |
|        |                  |         | 反射率         | 壁  | 70  | 50 | 30  | 10 | 70  | 50 | 30  | 10 | 70  | 50 | 30  | 10 | 70  | 50 | 30  | 10 | 0% |
|        |                  |         |             | 床  | 10% |    |     |    | 10% |    |     |    | 10% |    |     |    | 10% |    |     |    | 0% |
| 上方光束   | 24%              | 室指数     | 照明率 (X0.01) |    |     |    |     |    |     |    |     |    |     |    |     |    |     |    | ZCM |    |    |
| 下方光束   | 76%              |         |             |    |     |    |     |    |     |    |     |    |     |    |     |    |     |    |     |    |    |
| 保守率    | 良<br>中<br>否      | 0.83    | 0.6         | 47 | 34  | 25 | 19  | 44 | 32  | 24 | 19  | 40 | 29  | 22 | 17  | 35 | 26  | 20 | 16  | 12 |    |
|        |                  | 0.81    | 0.8         | 56 | 43  | 34 | 28  | 53 | 41  | 33 | 27  | 47 | 37  | 30 | 25  | 42 | 33  | 27 | 23  | 18 |    |
|        |                  |         | 1.0         | 62 | 50  | 41 | 34  | 59 | 47  | 39 | 33  | 52 | 43  | 36 | 30  | 46 | 39  | 33 | 28  | 23 |    |
|        |                  | 0.77    | 1.25        | 68 | 56  | 47 | 41  | 64 | 54  | 45 | 39  | 57 | 49  | 42 | 36  | 51 | 44  | 38 | 33  | 28 |    |
| 下方投影面積 | c m <sup>2</sup> | 1.5     | 72          | 61 | 53  | 46 | 68  | 58 | 51  | 44 | 61  | 53 | 46  | 41 | 55  | 48 | 42  | 38 | 32  |    |    |
|        |                  | 2.0     | 78          | 69 | 61  | 54 | 74  | 66 | 58  | 52 | 67  | 60 | 54  | 49 | 60  | 54 | 49  | 45 | 38  |    |    |
| 取付高さ   | 器具間隔最大限          |         | 2.5         | 82 | 74  | 67 | 60  | 78 | 70  | 64 | 58  | 71 | 64  | 59 | 54  | 63 | 58  | 54 | 50  | 42 |    |
|        | 横方向 (A)          | 縦方向 (B) | 3.0         | 85 | 77  | 71 | 65  | 81 | 74  | 68 | 63  | 73 | 68  | 63 | 58  | 66 | 62  | 57 | 54  | 46 |    |
| 1.5m   | 2.24m            | 1.9m    | 4.0         | 89 | 82  | 77 | 72  | 85 | 79  | 74 | 69  | 77 | 72  | 68 | 64  | 70 | 66  | 62 | 59  | 51 |    |
| 2      | 2.99             | 2.5     | 5.0         | 91 | 86  | 81 | 76  | 87 | 82  | 78 | 74  | 79 | 75  | 72 | 68  | 72 | 69  | 66 | 63  | 55 |    |
| 2.5    | 3.73             | 3.11    | 7.0         | 94 | 90  | 86 | 82  | 90 | 86  | 83 | 79  | 82 | 79  | 76 | 73  | 75 | 73  | 70 | 68  | 59 |    |
| 3      | 4.45             | 3.71    | 10.0        | 96 | 93  | 90 | 87  | 92 | 89  | 87 | 84  | 85 | 82  | 80 | 78  | 78 | 76  | 74 | 72  | 63 |    |

