

屋内照明器具特性

品番 (品名)	XLF433NNC(JYOUJI_WALL)	
光源	LED5000_85_3070 ×1	3070.0 1 m
管理番号	K0153254(2)DR1	
BZ分類	BZ7	

器具効率	100%	天井	80%				70%				50%				30%				0%				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	28%	反射率	床	10%				10%				10%				10%				0%			
下方光束	72%		室指数	照明率 (X0.01)																			
保守率	良 中 否 0.83 0.81 0.77	0.6	48	36	27	22	46	34	26	21	40	31	24	19	36	27	22	18	14				
		0.8	57	45	36	30	54	42	35	29	48	38	32	26	42	34	29	24	20				
		1.0	63	51	42	36	60	49	41	35	53	44	37	32	47	39	34	29	24				
		1.25	69	58	49	43	65	55	47	41	58	49	43	38	51	44	39	34	28				
下方投影面積	c m ²	1.5	73	62	54	48	69	59	52	46	61	53	47	42	54	48	43	38	32				
		2.0	79	69	62	56	74	66	59	53	66	60	54	49	59	54	49	45	37				
取付高さ	器具間隔最大限		2.5	82	74	67	61	78	71	64	59	70	64	59	54	62	57	53	49	41			
	横方向 (A)	縦方向 (B)	3.0	85	78	71	66	81	74	68	63	72	67	62	58	65	60	56	53	45			
1.5m	2 m	2.08 m	4.0	88	82	77	72	84	79	74	69	76	71	67	64	68	64	61	58	49			
2	2.65	2.64	5.0	91	86	81	77	86	82	77	73	78	74	71	67	70	67	64	62	52			
2.5	3.29	3.21	7.0	93	89	86	82	89	85	82	79	81	78	75	72	73	71	68	66	56			
3	3.94	3.81	10.0	96	93	90	87	91	89	86	83	83	81	79	77	75	73	72	70	60			

