

# 屋内照明器具特性

品番 (品名)	XLG422NGNJ ( J YOUJ I )														
光源	LED5000_85_2500 ×1 2500.0 lm														
管理番号	K0179166 ( 0 ) D 1														
BZ分類	BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	4 %	反射率	床	10 %				10 %				10 %				10 %				0 %	
下方光束	96 %		室指数	照明率 ( X0.01 ) ZCM																	
保守率	良	0.83	0.6	5.5	4.3	3.5	3.0	5.4	4.2	3.5	3.0	5.1	4.1	3.4	2.9	4.9	4.0	3.3	2.9	2.7	
	中	0.81	0.8	6.5	5.3	4.5	4.0	6.3	5.2	4.5	3.9	6.0	5.1	4.4	3.9	5.7	4.9	4.3	3.8	3.6	
	否	0.77	1.0	7.2	6.1	5.3	4.7	7.0	6.0	5.2	4.6	6.6	5.7	5.1	4.6	6.3	5.5	5.0	4.5	4.2	
			1.25	7.8	6.7	6.0	5.4	7.6	6.6	5.9	5.4	7.2	6.4	5.8	5.3	6.8	6.2	5.6	5.2	4.9	
下方投影面積			1.5	8.2	7.2	6.5	5.9	8.0	7.1	6.4	5.9	7.6	6.9	6.3	5.8	7.2	6.6	6.1	5.7	5.4	
等価発光面積			2.0	8.7	7.9	7.3	6.8	8.5	7.8	7.2	6.7	8.1	7.5	7.0	6.6	7.8	7.3	6.8	6.4	6.1	
取付高さ	器具間隔最大限		2.5	9.1	8.4	7.8	7.3	8.9	8.2	7.7	7.3	8.5	8.0	7.5	7.1	8.1	7.7	7.3	7.0	6.6	
	横方向 (A)	縦方向 (B)	3.0	9.3	8.7	8.2	7.8	9.1	8.6	8.1	7.7	8.7	8.3	7.9	7.5	8.4	8.0	7.7	7.3	7.0	
1.5m	1.96m	2.11m	4.0	9.6	9.2	8.7	8.4	9.5	9.0	8.6	8.3	9.1	8.7	8.4	8.1	8.7	8.4	8.1	7.9	7.5	
2	2.58	2.65	5.0	9.8	9.4	9.1	8.7	9.7	9.3	8.9	8.6	9.3	9.0	8.7	8.4	8.9	8.7	8.4	8.2	7.8	
2.5	3.21	3.22	7.0	10.1	9.8	9.5	9.2	9.9	9.6	9.3	9.1	9.5	9.3	9.1	8.9	9.2	9.0	8.8	8.6	8.3	
3	3.84	3.8	10.0	10.3	10.0	9.8	9.6	10.1	9.9	9.7	9.5	9.7	9.6	9.4	9.2	9.4	9.3	9.1	9.0	8.6	

