

| 屋内照明器具特性 | |
|----------|------------------------------|
| 品番 (品名) | XLF436PTNC(JYOUJI_WALL) |
| 光源 | LED5000_85_2980 x1 2980.0 lm |
| 管理番号 | K0153252(2)DR1 |
| BZ分類 | BZ8/0.9/BZ7 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|---------|-----------------|-------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 25% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 75% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 | 0.83 | 0.6 | 47 | 34 | 25 | 19 | 44 | 32 | 24 | 18 | 39 | 29 | 22 | 17 | 35 | 26 | 20 | 16 | 12 |
| | 中 | 0.81 | 0.8 | 56 | 43 | 34 | 27 | 52 | 41 | 32 | 26 | 47 | 37 | 30 | 24 | 41 | 33 | 27 | 22 | 18 |
| | 否 | 0.77 | 1.0 | 62 | 49 | 40 | 33 | 58 | 47 | 38 | 32 | 52 | 42 | 35 | 30 | 46 | 38 | 32 | 27 | 22 |
| | | | 1.25 | 68 | 56 | 47 | 40 | 64 | 53 | 45 | 39 | 57 | 48 | 41 | 36 | 51 | 43 | 38 | 33 | 27 |
| 下方投影面積 | | cm ² | 1.5 | 72 | 61 | 52 | 45 | 68 | 58 | 50 | 44 | 61 | 53 | 46 | 40 | 54 | 47 | 42 | 37 | 31 |
| 等価発光面積 | | cm ² | 2.0 | 78 | 68 | 60 | 54 | 74 | 65 | 58 | 52 | 66 | 59 | 53 | 48 | 59 | 53 | 48 | 44 | 37 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 82 | 73 | 66 | 60 | 78 | 70 | 63 | 58 | 70 | 64 | 58 | 53 | 63 | 58 | 53 | 49 | 42 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 85 | 77 | 71 | 65 | 81 | 74 | 68 | 62 | 73 | 67 | 62 | 58 | 65 | 61 | 57 | 53 | 45 |
| 1.5m | 2.29m | 2.08m | 4.0 | 88 | 82 | 77 | 72 | 84 | 79 | 73 | 69 | 77 | 72 | 68 | 64 | 69 | 65 | 62 | 59 | 50 |
| 2 | 3.02 | 2.65 | 5.0 | 91 | 85 | 81 | 76 | 87 | 82 | 77 | 73 | 79 | 75 | 71 | 68 | 72 | 68 | 65 | 62 | 54 |
| 2.5 | 3.76 | 3.23 | 7.0 | 94 | 90 | 86 | 82 | 90 | 86 | 82 | 79 | 82 | 79 | 76 | 73 | 75 | 72 | 70 | 67 | 58 |
| 3 | 4.5 | 3.83 | 10.0 | 96 | 93 | 90 | 87 | 92 | 89 | 86 | 84 | 84 | 82 | 80 | 77 | 77 | 75 | 73 | 71 | 62 |

