

屋内照明器具特性

品番 (品名)	XLG453PGN(JYOUJI)	
光源	LED5000_85_5040 x1	5040.0 lm
管理番号	K0176625(0)DR1	
BZ分類	BZ5/1.8/BZ4	

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	床	10%				10%				10%				10%				0%
下方光束	100%		室指数	照明率 (X0.01)																ZCM
保守率	良 0.81	0.6	57	45	37	32	56	44	37	32	53	43	36	32	51	42	36	31	29	
	中 0.77	0.8	67	56	48	42	66	55	48	42	63	54	47	42	60	52	46	42	40	
	否 0.68	1.0	74	63	56	50	72	62	55	50	69	61	54	49	67	59	54	49	47	
		1.25	80	70	63	58	78	69	63	57	75	68	62	57	72	66	61	56	54	
下方投影面積	c m ²	1.5	84	75	69	63	82	74	68	63	79	72	67	62	76	71	66	62	59	
		2.0	90	83	77	72	88	81	76	71	85	79	75	71	82	77	73	70	67	
取付高さ	器具間隔最大限		2.5	93	87	82	78	92	86	81	77	89	84	80	76	86	82	78	75	73
	横方向 (A)	縦方向 (B)	3.0	96	90	86	82	94	89	85	81	91	87	83	80	88	85	82	79	76
1.5m	1.94 m	2.12 m	4.0	99	95	91	88	97	94	90	87	94	91	88	86	92	89	87	84	82
2	2.56	2.67	5.0	101	97	94	91	99	96	93	91	96	94	91	89	94	92	90	88	85
2.5	3.18	3.24	7.0	103	100	98	96	101	99	97	95	99	97	95	93	96	95	93	92	89
3	3.8	3.83	10.0	104	103	101	99	103	101	100	98	101	99	98	97	98	97	96	95	92

