

屋内照明器具特性

品番 (品名)	XLG462NGNJ (J YOUJ I)														
光源	LED5000_85_6900 x1 6900.0 1 m														
管理番号	K0179166 (0) D 1														
BZ分類	BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	4 %	室指数	照明率 (X0.01)																ZCM		
下方光束	96 %																				
保守率	良 0.83 中 0.81 否 0.77	0.6	55	43	35	30	54	42	35	30	51	41	34	29	49	40	33	29	27		
		0.8	65	53	45	40	63	52	45	39	60	51	44	39	57	49	43	38	36		
		1.0	72	61	53	47	70	60	52	46	66	57	51	46	63	55	50	45	42		
		1.25	78	67	60	54	76	66	59	54	72	64	58	53	68	62	56	52	49		
下方投影面積 等価発光面積	c m ²	1.5	82	72	65	59	80	71	64	59	76	69	63	58	72	66	61	57	54		
		2.0	87	79	73	68	85	78	72	67	81	75	70	66	78	73	68	64	61		
		2.5	91	84	78	73	89	82	77	73	85	80	75	71	81	77	73	70	66		
取付高さ	器具間隔最大限		3.0	93	87	82	78	91	86	81	77	87	83	79	75	84	80	77	73	70	
	横方向 (A)	縦方向 (B)																			
1.5m	1.96 m	2.11 m	4.0	96	92	87	84	95	90	86	83	91	87	84	81	87	84	81	79	75	
2	2.58	2.65	5.0	98	94	91	87	97	93	89	86	93	90	87	84	89	87	84	82	78	
2.5	3.21	3.22	7.0	101	98	95	92	99	96	93	91	95	93	91	89	92	90	88	86	83	
3	3.84	3.8	10.0	103	100	98	96	101	99	97	95	97	96	94	92	94	93	91	90	86	

