

# 屋内照明器具特性

|         |                    |  |  |  |  |           |  |  |  |  |
|---------|--------------------|--|--|--|--|-----------|--|--|--|--|
| 品番 (品名) | XL X4 5 0 KB WC    |  |  |  |  |           |  |  |  |  |
| 光源      | LED4000_85_3800 x1 |  |  |  |  | 3800.0 lm |  |  |  |  |
| 管理番号    | K0130921 (* ) DB 1 |  |  |  |  |           |  |  |  |  |
| BZ分類    | BZ5                |  |  |  |  |           |  |  |  |  |

|        |             |                 |               |      |      |      |      |      |      |     |      |      |     |     |      |     |     |     |     |     |     |
|--------|-------------|-----------------|---------------|------|------|------|------|------|------|-----|------|------|-----|-----|------|-----|-----|-----|-----|-----|-----|
| 器具効率   | 100 %       | 天井              | 80 %          |      |      |      | 70 % |      |      |     | 50 % |      |     |     | 30 % |     |     |     | 0 % |     |     |
|        |             | 壁               | 70            | 50   | 30   | 10   | 70   | 50   | 30   | 10  | 70   | 50   | 30  | 10  | 70   | 50  | 30  | 10  | 0 % |     |     |
| 上方光束   | 0 %         | 床               | 10 %          |      |      |      | 10 % |      |      |     | 10 % |      |     |     | 10 % |     |     |     | 0 % |     |     |
| 下方光束   | 100 %       | 室指数             | 照明率 ( X0.01 ) |      |      |      |      |      |      |     |      |      |     |     |      |     |     |     | ZCM |     |     |
| 保守率    | 良<br>中<br>否 | 0.81            | 0.6           | 5.6  | 4.4  | 3.6  | 3.1  | 5.5  | 4.3  | 3.6 | 3.0  | 5.2  | 4.2 | 3.5 | 3.0  | 5.0 | 4.1 | 3.5 | 3.0 | 2.8 |     |
|        |             | 0.77            | 0.8           | 6.6  | 5.5  | 4.7  | 4.1  | 6.5  | 5.4  | 4.6 | 4.1  | 6.2  | 5.2 | 4.6 | 4.1  | 5.9 | 5.1 | 4.5 | 4.0 | 3.8 |     |
|        |             | 0.68            | 1.0           | 7.3  | 6.2  | 5.4  | 4.8  | 7.1  | 6.1  | 5.4 | 4.8  | 6.8  | 6.0 | 5.3 | 4.8  | 6.6 | 5.8 | 5.2 | 4.8 | 4.5 |     |
|        |             |                 | 1.25          | 7.9  | 6.9  | 6.2  | 5.6  | 7.7  | 6.8  | 6.1 | 5.6  | 7.4  | 6.6 | 6.0 | 5.5  | 7.1 | 6.5 | 5.9 | 5.5 | 5.3 |     |
| 下方投影面積 |             | cm <sup>2</sup> |               | 1.5  | 8.3  | 7.4  | 6.7  | 6.2  | 8.1  | 7.3 | 6.7  | 6.1  | 7.8 | 7.1 | 6.6  | 6.1 | 7.6 | 6.9 | 6.5 | 6.0 | 5.8 |
| 等価発光面積 |             | cm <sup>2</sup> |               | 2.0  | 8.9  | 8.1  | 7.5  | 7.0  | 8.7  | 8.0 | 7.5  | 7.0  | 8.4 | 7.8 | 7.3  | 6.9 | 8.1 | 7.6 | 7.2 | 6.8 | 6.6 |
| 取付高さ   | 器具間隔最大限     |                 | 2.5           | 9.2  | 8.6  | 8.1  | 7.6  | 9.1  | 8.5  | 8.0 | 7.6  | 8.8  | 8.3 | 7.9 | 7.5  | 8.5 | 8.1 | 7.7 | 7.4 | 7.1 |     |
|        | 横方向 (A)     | 縦方向 (B)         | 3.0           | 9.5  | 8.9  | 8.5  | 8.1  | 9.3  | 8.8  | 8.4 | 8.0  | 9.0  | 8.6 | 8.2 | 7.9  | 8.8 | 8.4 | 8.1 | 7.8 | 7.5 |     |
| 1.5m   | 1.97m       | 2.17m           | 4.0           | 9.8  | 9.4  | 9.0  | 8.7  | 9.7  | 9.3  | 8.9 | 8.6  | 9.4  | 9.0 | 8.7 | 8.5  | 9.1 | 8.8 | 8.6 | 8.3 | 8.1 |     |
| 2      | 2.6         | 2.74            | 5.0           | 10.0 | 9.7  | 9.3  | 9.0  | 9.9  | 9.5  | 9.2 | 9.0  | 9.6  | 9.3 | 9.1 | 8.8  | 9.3 | 9.1 | 8.9 | 8.7 | 8.4 |     |
| 2.5    | 3.23        | 3.33            | 7.0           | 10.2 | 10.0 | 9.7  | 9.5  | 10.1 | 9.8  | 9.6 | 9.4  | 9.8  | 9.6 | 9.4 | 9.2  | 9.6 | 9.4 | 9.2 | 9.1 | 8.8 |     |
| 3      | 3.86        | 3.93            | 10.0          | 10.4 | 10.2 | 10.0 | 9.9  | 10.3 | 10.1 | 9.9 | 9.8  | 10.0 | 9.9 | 9.7 | 9.6  | 9.8 | 9.6 | 9.5 | 9.4 | 9.1 |     |

