

屋内照明器具特性		
品番（品名）	S F 0 7 2 W K	
光源	L E D 2 7 0 0 _ 7 0 _ 2 3 0 x 1 2 3 0 . 0 l m	
管理番号	K 0 1 5 8 5 3 9 (0) D R 1	
B Z 分類	B Z 1 0	

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
上方光束		1 0 0 %		床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
下方光束		0 %	室指数	照明率 (X 0 . 0 1)																	Z C M
保守率		良 0 . 6 7	0 . 6	4 3	3 3	2 6	2 2	3 7	2 8	2 3	1 9	2 5	1 9	1 6	1 3	1 4	1 1	9	8	0	
		中 0 . 6 3	0 . 8	5 1	4 1	3 4	2 9	4 3	3 5	2 9	2 5	2 9	2 4	2 1	1 8	1 7	1 4	1 2	1 0	0	
		否 0 . 5 6	1 . 0	5 6	4 7	4 0	3 5	4 8	4 0	3 5	3 1	3 3	2 8	2 4	2 2	1 9	1 6	1 4	1 3	0	
		下方投影面積	c m ²	1 . 2 5	6 1	5 3	4 7	4 2	5 2	4 6	4 0	3 6	3 6	3 1	2 8	2 5	2 0	1 8	1 6	1 5	0
1 . 5	6 5			5 7	5 1	4 6	5 6	4 9	4 4	4 0	3 8	3 4	3 1	2 8	2 2	2 0	1 8	1 7	0		
等価発光面積		c m ²	2 . 0	7 0	6 3	5 8	5 4	6 0	5 5	5 0	4 7	4 1	3 8	3 5	3 3	2 4	2 2	2 1	1 9	0	
取付 高さ	器具間隔最大限		2 . 5	7 3	6 7	6 3	5 9	6 3	5 8	5 4	5 1	4 3	4 0	3 8	3 6	2 5	2 3	2 2	2 1	0	
	横方向 (A)	縦方向 (B)	3 . 0	7 5	7 0	6 6	6 2	6 4	6 1	5 7	5 4	4 4	4 2	4 0	3 8	2 6	2 4	2 3	2 2	0	
H m	0 . 2 0 H m	0 . 2 0 H m	4 . 0	7 8	7 4	7 1	6 7	6 7	6 4	6 1	5 9	4 6	4 4	4 3	4 1	2 7	2 6	2 5	2 4	0	
			5 . 0	7 9	7 6	7 3	7 1	6 8	6 6	6 4	6 1	4 7	4 6	4 4	4 3	2 7	2 7	2 6	2 5	0	
			7 . 0	8 1	7 9	7 7	7 5	7 0	6 8	6 6	6 5	4 9	4 7	4 6	4 5	2 8	2 8	2 7	2 7	0	
			1 0 . 0	8 3	8 1	8 0	7 8	7 2	7 0	6 9	6 8	5 0	4 9	4 8	4 7	2 9	2 8	2 8	2 8	0	

