

屋内照明器具特性

品番 (品名)	S F 9 6 5 S F									
光源	LDA4L-H-E17/S/4 x1 440.0 lm									
管理番号	K0123365 (0) DB 1									
B Z 分類	B Z 9									

器具効率		8 9 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束 下方光束		7 5 % 1 4 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 3	0 . 6	3 9	2 9	2 2	1 8	3 4	2 5	2 0	1 6	2 4	1 8	1 5	1 2	1 6	1 2	1 0	8	1
			0 . 6	0 . 8	4 6	3 6	2 9	2 5	4 0	3 2	2 6	2 2	2 9	2 3	1 9	1 6	1 9	1 5	1 3	1 1	2
			0 . 5 6	1 . 0	5 1	4 2	3 5	3 0	4 4	3 6	3 1	2 7	3 2	2 7	2 3	2 0	2 1	1 8	1 5	1 3	3
				1 . 2 5	5 5	4 7	4 1	3 6	4 8	4 1	3 6	3 2	3 5	3 0	2 7	2 4	2 3	2 0	1 8	1 6	4
下方投影面積		c m ²	1 . 5	5 9	5 1	4 5	4 0	5 1	4 5	4 0	3 6	3 7	3 3	2 9	2 7	2 5	2 2	2 0	1 8	4	
等価発光面積		c m ²	2 . 0	6 3	5 7	5 1	4 7	5 5	5 0	4 5	4 1	4 1	3 7	3 4	3 1	2 7	2 5	2 3	2 1	6	
取付 高さ	器具間隔最大限		2 . 5	6 6	6 0	5 6	5 1	5 8	5 3	4 9	4 6	4 3	3 9	3 7	3 4	2 9	2 6	2 5	2 3	6	
	横方向 (A)	縦方向 (B)	3 . 0	6 8	6 3	5 9	5 5	6 0	5 6	5 2	4 9	4 4	4 1	3 9	3 7	3 0	2 8	2 6	2 5	7	
H m	0 . 0 0 H m	0 . 0 0 H m	4 . 0	7 1	6 7	6 3	6 0	6 2	5 9	5 6	5 3	4 6	4 4	4 2	4 0	3 1	3 0	2 8	2 7	8	
			5 . 0	7 2	6 9	6 6	6 3	6 4	6 1	5 8	5 6	4 8	4 6	4 4	4 2	3 2	3 1	3 0	2 9	9	
			7 . 0	7 4	7 2	6 9	6 7	6 6	6 4	6 2	6 0	4 9	4 8	4 6	4 5	3 3	3 2	3 1	3 1	1 0	
			1 0 . 0	7 6	7 4	7 2	7 0	6 7	6 6	6 4	6 3	5 0	4 9	4 8	4 7	3 4	3 4	3 3	3 2	1 1	

