

屋内照明器具特性

品番 (品名)	XLG451VGN(JYOUJI)									
光源	LED5000_85_5040 x1 5040.0 lm									
管理番号	K0176622(0)DR1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	0%	反射率	10%				10%				10%				10%				0%				
下方光束	100%		床	10%				10%				10%				10%				0%			
		室指数	照明率 (X0.01)																				ZCM
保守率	良	0.81	0.6	5.6	4.4	3.6	3.0	5.5	4.3	3.6	3.0	5.2	4.2	3.5	3.0	5.0	4.1	3.5	3.0	2.8			
	中	0.77	0.8	6.6	5.4	4.6	4.1	6.5	5.4	4.6	4.0	6.2	5.2	4.5	4.0	5.9	5.1	4.5	4.0	3.8			
	否	0.68	1.0	7.3	6.2	5.4	4.8	7.1	6.1	5.3	4.8	6.8	5.9	5.3	4.7	6.5	5.8	5.2	4.7	4.5			
			1.25	7.9	6.9	6.1	5.5	7.7	6.8	6.1	5.5	7.4	6.6	6.0	5.5	7.1	6.4	5.9	5.4	5.2			
下方投影面積		cm ²	1.5	8.3	7.4	6.7	6.1	8.1	7.3	6.6	6.1	7.8	7.1	6.5	6.0	7.5	6.9	6.4	6.0	5.7			
等価発光面積		cm ²	2.0	8.9	8.1	7.5	7.0	8.7	8.0	7.4	6.9	8.4	7.8	7.3	6.8	8.1	7.6	7.1	6.8	6.5			
取付高さ	器具間隔最大限		2.5	9.2	8.6	8.0	7.6	9.1	8.5	7.9	7.5	8.7	8.2	7.8	7.4	8.5	8.0	7.6	7.3	7.0			
	横方向 (A)	縦方向 (B)	3.0	9.5	8.9	8.4	8.0	9.3	8.8	8.3	7.9	9.0	8.6	8.2	7.8	8.7	8.4	8.0	7.7	7.4			
1.5m	1.96m	2.12m	4.0	9.8	9.4	9.0	8.6	9.7	9.2	8.9	8.5	9.4	9.0	8.7	8.4	9.1	8.8	8.5	8.3	8.0			
2	2.59	2.67	5.0	10.0	9.6	9.3	9.0	9.9	9.5	9.2	8.9	9.6	9.3	9.0	8.8	9.3	9.1	8.8	8.6	8.3			
2.5	3.22	3.23	7.0	10.2	10.0	9.7	9.5	10.1	9.8	9.6	9.4	9.8	9.6	9.4	9.2	9.6	9.4	9.2	9.0	8.8			
3	3.85	3.81	10.0	10.4	10.2	10.0	9.8	10.3	10.1	9.9	9.8	10.0	9.9	9.7	9.6	9.8	9.6	9.5	9.4	9.1			

