

屋内照明器具特性	
品番 (品名)	S L B 1 5 1 3 4 B
光源	LED2700_70_441 x1 441.0 lm
管理番号	K0134272 (0) DB 1
B Z 分類	B Z 5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		18 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		82 %																							
保守率		良 中 否	0.67	0.6	54	41	34	28	51	40	33	28	47	38	31	27	43	35	30	26	23				
			0.63	0.8	63	52	44	38	61	50	43	38	56	47	41	36	52	44	39	35	31				
			0.56	1.0	70	59	51	46	67	57	50	45	62	54	48	43	57	50	45	41	37				
				1.25	76	66	59	53	73	64	57	52	67	60	54	50	62	56	51	47	43				
下方投影面積		cm ²		1.5	80	71	64	59	77	69	62	57	71	64	59	55	66	60	56	52	47				
等価発光面積			cm ²	2.0	85	78	72	67	82	76	70	65	76	71	66	62	71	66	63	59	54				
取付 高さ	器具間隔最大限		2.5	89	83	77	73	86	80	75	71	80	75	71	67	74	70	67	64	58					
	横方向 (A)		縦方向 (B)		3.0	91	86	81	77	88	83	79	75	82	78	74	71	76	73	70	68	61			
H m	1.32 H m		1.32 H m		4.0	94	90	86	83	91	87	84	81	85	82	79	76	80	77	75	72	66			
					5.0	96	93	89	86	93	90	87	84	87	84	82	80	81	79	77	75	69			
					7.0	99	96	93	91	95	93	91	88	89	87	85	84	84	82	81	79	72			
					10.0	100	98	96	95	97	95	94	92	91	90	88	87	85	84	83	82	75			

