

屋内照明器具特性	
品番 (品名)	S L B 1 5 1 3 4 W
光源	LED2700_70_441 x1 441.0 lm
管理番号	K0134272 (0) DB 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		1 8 % 8 2 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6	5 4	4 1	3 4	2 8	5 1	4 0	3 3	2 8	4 7	3 8	3 1	2 7	4 3	3 5	3 0	2 6	2 3		
			0 . 8	6 3	5 2	4 4	3 8	6 1	5 0	4 3	3 8	5 6	4 7	4 1	3 6	5 2	4 4	3 9	3 5	3 1		
			1 . 0	7 0	5 9	5 1	4 6	6 7	5 7	5 0	4 5	6 2	5 4	4 8	4 3	5 7	5 0	4 5	4 1	3 7		
			0 . 5 6	1 . 2 5	7 6	6 6	5 9	5 3	7 3	6 4	5 7	5 2	6 7	6 0	5 4	5 0	6 2	5 6	5 1	4 7	4 3	
下方投影面積		cm ²	1 . 5	8 0	7 1	6 4	5 9	7 7	6 9	6 2	5 7	7 1	6 4	5 9	5 5	6 6	6 0	5 6	5 2	4 7		
等価発光面積		cm ²	2 . 0	8 5	7 8	7 2	6 7	8 2	7 6	7 0	6 5	7 6	7 1	6 6	6 2	7 1	6 6	6 3	5 9	5 4		
取付 高さ	器具間隔最大限		2 . 5	8 9	8 3	7 7	7 3	8 6	8 0	7 5	7 1	8 0	7 5	7 1	6 7	7 4	7 0	6 7	6 4	5 8		
	横方向 (A) 縦方向 (B)		3 . 0	9 1	8 6	8 1	7 7	8 8	8 3	7 9	7 5	8 2	7 8	7 4	7 1	7 6	7 3	7 0	6 8	6 1		
H m	1 . 3 2 H m	1 . 3 2 H m	4 . 0	9 4	9 0	8 6	8 3	9 1	8 7	8 4	8 1	8 5	8 2	7 9	7 6	8 0	7 7	7 5	7 2	6 6		
			5 . 0	9 6	9 3	8 9	8 6	9 3	9 0	8 7	8 4	8 7	8 4	8 2	8 0	8 1	7 9	7 7	7 5	6 9		
			7 . 0	9 9	9 6	9 3	9 1	9 5	9 3	9 1	8 8	8 9	8 7	8 5	8 4	8 4	8 2	8 1	7 9	7 2		
			1 0 . 0	1 0 0	9 8	9 6	9 5	9 7	9 5	9 4	9 2	9 1	9 0	8 8	8 7	8 5	8 4	8 3	8 2	7 5		

