

屋内照明器具特性

品番 (品名)	XLX457BHNP_55DEG									
光源	LED5000_85_4380 x1 4380.0 lm									
管理番号	K0145761 (*) DB1									
BZ分類	BZ5/1.4/BZ4									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																														
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																														
		床	10 %				10 %				10 %				10 %				0 %																														
上方光束	0 %	室指数																照明率 (X0.01)																ZCM															
下方光束	100 %																																																
保守率	良 中 否	0.81	0.6	5.6	4.4	3.6	3.1	5.5	4.4	3.6	3.1	5.3	4.2	3.6	3.1	5.1	4.1	3.5	3.0	2.9																													
		0.77	0.8	6.7	5.5	4.8	4.2	6.5	5.5	4.7	4.2	6.3	5.3	4.7	4.2	6.0	5.2	4.6	4.1	3.9																													
		0.68	1.0	7.4	6.3	5.6	5.0	7.2	6.2	5.5	5.0	6.9	6.1	5.4	4.9	6.7	5.9	5.4	4.9	4.7																													
			1.25	8.0	7.0	6.3	5.8	7.8	7.0	6.3	5.8	7.5	6.8	6.2	5.7	7.3	6.6	6.1	5.7	5.4																													
下方投影面積	c m ²	1.5	8.4	7.6	6.9	6.4	8.3	7.5	6.8	6.3	8.0	7.3	6.7	6.3	7.7	7.1	6.6	6.2	6.0																														
		2.0	9.0	8.3	7.7	7.2	8.8	8.2	7.6	7.2	8.5	8.0	7.5	7.1	8.3	7.8	7.4	7.0	6.8																														
取付高さ	器具間隔最大限		2.5	9.3	8.7	8.2	7.8	9.2	8.6	8.2	7.8	8.9	8.4	8.0	7.7	8.6	8.2	7.9	7.6	7.3																													
	横方向 (A)	縦方向 (B)	3.0	9.6	9.1	8.6	8.2	9.4	9.0	8.5	8.2	9.1	8.7	8.4	8.1	8.9	8.5	8.2	8.0	7.7																													
1.5m	1.96 m	2.17 m	4.0	9.9	9.5	9.1	8.8	9.7	9.4	9.0	8.7	9.5	9.1	8.9	8.6	9.2	8.9	8.7	8.5	8.2																													
2	2.59	2.74	5.0	10.1	9.7	9.4	9.2	9.9	9.6	9.3	9.1	9.7	9.4	9.2	8.9	9.4	9.2	9.0	8.8	8.5																													
2.5	3.22	3.33	7.0	10.3	10.0	9.8	9.6	10.1	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.6	9.5	9.3	9.2	8.9																													
3	3.85	3.94	10.0	10.4	10.3	10.1	9.9	10.3	10.1	10.0	9.8	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2																													

