

# 屋内照明器具特性

|         |                             |  |  |  |  |  |  |  |  |  |
|---------|-----------------------------|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XLG463DGN(JYOUJI)           |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_6900 x1 6900.0lm |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0177481(0)D 1              |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ5                         |  |  |  |  |  |  |  |  |  |

|        |         |         |              |      |      |     |     |      |     |     |     |     |     |     |     |     |     |     |     |     |    |
|--------|---------|---------|--------------|------|------|-----|-----|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| 器具効率   | 100%    | 天井      | 80%          |      |      |     | 70% |      |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |    |
|        |         |         | 反射率          | 壁    | 70   | 50  | 30  | 10   | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0% |
|        |         |         |              | 床    | 10%  |     |     |      | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
| 上方光束   | 4%      | 室指数     | 照明率 ( X0.01) |      |      |     |     |      |     |     |     |     |     |     |     |     |     |     | ZCM |     |    |
| 下方光束   | 96%     |         |              |      |      |     |     |      |     |     |     |     |     |     |     |     |     |     |     |     |    |
| 保守率    | 良       | 0.83    | 0.6          | 5.5  | 4.3  | 3.5 | 3.0 | 5.4  | 4.2 | 3.5 | 3.0 | 5.1 | 4.1 | 3.4 | 2.9 | 4.9 | 4.0 | 3.3 | 2.9 | 2.7 |    |
|        | 中       | 0.81    | 0.8          | 6.5  | 5.4  | 4.5 | 4.0 | 6.4  | 5.3 | 4.5 | 3.9 | 6.0 | 5.1 | 4.4 | 3.9 | 5.7 | 4.9 | 4.3 | 3.8 | 3.6 |    |
|        | 否       | 0.77    | 1.0          | 7.2  | 6.1  | 5.3 | 4.7 | 7.0  | 6.0 | 5.2 | 4.7 | 6.6 | 5.8 | 5.1 | 4.6 | 6.3 | 5.6 | 5.0 | 4.5 | 4.3 |    |
|        |         |         | 1.25         | 7.8  | 6.8  | 6.0 | 5.4 | 7.6  | 6.6 | 5.9 | 5.4 | 7.2 | 6.4 | 5.8 | 5.3 | 6.9 | 6.2 | 5.6 | 5.2 | 4.9 |    |
| 下方投影面積 |         |         | 1.5          | 8.2  | 7.2  | 6.5 | 6.0 | 8.0  | 7.1 | 6.4 | 5.9 | 7.6 | 6.9 | 6.3 | 5.8 | 7.3 | 6.6 | 6.1 | 5.7 | 5.4 |    |
|        | 等価発光面積  |         | 2.0          | 8.7  | 7.9  | 7.3 | 6.8 | 8.5  | 7.8 | 7.2 | 6.7 | 8.2 | 7.5 | 7.0 | 6.6 | 7.8 | 7.3 | 6.8 | 6.5 | 6.1 |    |
| 取付高さ   | 器具間隔最大限 |         | 2.5          | 9.1  | 8.4  | 7.8 | 7.3 | 8.9  | 8.3 | 7.7 | 7.3 | 8.5 | 8.0 | 7.5 | 7.1 | 8.2 | 7.7 | 7.3 | 7.0 | 6.6 |    |
|        | 横方向 (A) | 縦方向 (B) | 3.0          | 9.3  | 8.7  | 8.2 | 7.8 | 9.1  | 8.6 | 8.1 | 7.7 | 8.8 | 8.3 | 7.9 | 7.5 | 8.4 | 8.0 | 7.7 | 7.4 | 7.0 |    |
| 1.5m   | 1.96m   | 2.12m   | 4.0          | 9.7  | 9.2  | 8.7 | 8.4 | 9.5  | 9.0 | 8.6 | 8.3 | 9.1 | 8.7 | 8.4 | 8.1 | 8.8 | 8.4 | 8.2 | 7.9 | 7.5 |    |
| 2      | 2.58    | 2.66    | 5.0          | 9.9  | 9.5  | 9.1 | 8.7 | 9.7  | 9.3 | 9.0 | 8.6 | 9.3 | 9.0 | 8.7 | 8.4 | 9.0 | 8.7 | 8.5 | 8.2 | 7.9 |    |
| 2.5    | 3.21    | 3.22    | 7.0          | 10.1 | 9.8  | 9.5 | 9.2 | 9.9  | 9.6 | 9.4 | 9.1 | 9.6 | 9.3 | 9.1 | 8.9 | 9.2 | 9.0 | 8.8 | 8.7 | 8.3 |    |
| 3      | 3.84    | 3.8     | 10.0         | 10.3 | 10.0 | 9.8 | 9.6 | 10.1 | 9.9 | 9.7 | 9.5 | 9.8 | 9.6 | 9.4 | 9.2 | 9.4 | 9.3 | 9.1 | 9.0 | 8.6 |    |

