

# 屋内照明器具特性

品番 (品名)	PAV12545 WWWP40 + NTS90354		
光源	LED4000_70_1635 ×1	1635.0 lm	
管理番号	K0179719 (0) DR1		
BZ分類	BZ1		

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
下方光束	100%	床	10%				10%				10%				10%				0%				
室指数	照明率 ( X0.01 )																			ZCM			
保守率	良	0.63	0.6	0.56	0.6	76	68	63	60	75	68	63	60	74	67	63	60	72	67	63	60	58	
	中	0.6	0.6	0.6	0.8	84	77	73	69	83	77	72	69	81	76	72	69	80	75	71	69	67	
	否	0.56	0.56	0.56	1.0	89	83	79	75	88	82	78	75	86	81	78	75	84	80	77	74	73	
下方投影面積	等価発光面積	cm <sup>2</sup>	cm <sup>2</sup>	1.25	93	88	84	81	92	87	83	80	90	86	83	80	88	85	82	79	78		
				1.5	96	91	87	84	95	90	87	84	93	89	86	84	91	88	85	83	81		
取付高さ	器具間隔最大限		Hm	0.51Hm	0.85Hm	2.0	99	95	92	90	98	94	92	89	96	93	90	88	94	91	89	87	86
	Hm	Hm				2.5	101	98	95	93	100	97	94	92	98	95	93	91	96	94	92	90	88
Hm			Hm	Hm	Hm	Hm	3.0	102	100	97	95	101	99	96	95	99	97	95	93	97	95	94	92
	4.0	104					102	100	98	103	101	99	98	100	99	97	96	98	97	96	95	93	
Hm	Hm	Hm	Hm	Hm	Hm	5.0	105	103	102	100	104	102	101	99	101	100	99	98	99	98	97	96	94
						7.0	106	105	103	102	105	104	102	101	102	102	101	100	100	99	98	96	
Hm	Hm	Hm	Hm	Hm	Hm	10.0	107	106	105	104	105	105	104	103	103	103	102	101	101	100	97		

