

屋内照明器具特性

品番 (品名)	SLB15782 + SLK22006 + SLK290	
光源	LLD2411LCB1 ×1	500.0 lm
管理番号	K0193681(0)DB1	
BZ分類	BZ1/4.5/BZ2	

器具効率	99%	天井	80%				70%				50%				30%				0%		
	上方光束		7%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	92%	床	10%				10%				10%				10%				0%		
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	等価発光面積	cm ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	89	92	95	97	98	100	101	102	103
		cm ²		89	92	95	97	98	100	101	102	103									
取付高さ	器具間隔最大限		Hm		0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	
	横方向 (A)	縦方向 (B)	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	0.74Hm	

