

屋内照明器具特性

品番 (品名)	SLB15782+SLK22006+SLK290	
光源	LLD2411LCB1 ×1 500.0 lm	
管理番号	K0193061(0)DB1	
BZ分類	BZ4/0.7/BZ5/3.5/BZ6	

器具効率	89%	天井	80%				70%				50%				30%				0%														
	上方光束		26%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%												
	下方光束		63%		床	10%				10%				10%				10%				0%											
室指数	照明率 (X0.01)																			ZCM													
保守率	良	0.63	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	48	38	32	27	46	37	31	27	41	34	29	25	37	31	27	24	20		
	中	0.6	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	55	46	39	34	53	44	38	33	47	40	35	31	43	37	32	29	25		
	否	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	60	51	45	40	57	49	43	38	51	45	40	36	46	41	37	33	28		
	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	65	56	50	45	62	54	48	43	55	49	44	40	50	45	41	37	32			
下方投影面積	c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		
	c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		c m ²		
取付高さ	器具間隔最大限		H m		H m		H m		H m		H m		H m		H m		H m		H m		H m		H m		H m		H m		H m		H m		
	H m		H m		H m		H m		H m		H m		H m		H m		H m		H m		H m		H m		H m		H m		H m		H m		
0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m	
0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m		0.60H m	

