

# 屋内照明器具特性

品番 (品名)	SLB15782 + SLK22006 + SLK290	
光源	LLD2421LCB1 ×1                      500.0 l m	
管理番号	K0193692 ( 0 ) DB 1	
BZ分類	BZ1 / 1.1 / BZ2 / 3.5 / BZ3	

器具効率	93 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 9 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	84 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 ( X 0.01 )																			ZCM
保守率	良 0.63	0.6	0.6	66	58	53	50	65	58	53	50	63	56	52	49	60	55	51	49	47
	中 0.6	0.6	0.8	73	65	60	57	71	65	60	56	68	63	59	56	66	61	58	55	53
	否 0.56	0.6	1.0	77	70	65	62	75	69	65	61	72	67	63	60	69	65	62	59	57
下方投影面積	c m <sup>2</sup>	1.25	81	75	70	66	79	73	69	66	76	71	67	64	73	69	66	63	60	
		1.5	83	78	73	70	81	76	72	69	78	74	70	68	75	71	69	66	63	
等価発光面積	c m <sup>2</sup>	2.0	87	82	78	75	85	80	77	74	81	78	75	72	78	75	72	70	67	
		2.5	89	85	81	78	87	83	80	77	83	80	77	75	80	77	75	73	70	
取付高さ	器具間隔最大限		3.0	90	87	83	81	88	85	82	80	84	82	79	77	81	79	77	75	71
H m	横方向 ( A )	縦方向 ( B )	4.0	92	89	87	84	90	87	85	83	86	84	82	80	83	81	79	78	74
	0.48 H m	0.51 H m	5.0	93	91	88	86	91	89	87	85	87	86	84	82	84	82	81	80	75
			7.0	95	93	91	89	93	91	89	88	89	87	86	85	85	84	83	82	77
			10.0	96	94	93	91	94	92	91	90	90	89	88	87	86	85	84	84	79

