

屋内照明器具特性	
品番 (品名)	SLB15782+SLK22007+SLK290
光源	LLD2401LCB1 ×1 500.0 lm
管理番号	K0192484 (1) DR1
BZ分類	BZ1

器具効率	39%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	39%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	3.2	2.9	2.8	2.7	3.2	2.9	2.8	2.7	3.1	2.9	2.8	2.7	3.1	2.9	2.7	2.7	2.6
	中	0.63	0.8	3.4	3.2	3.1	3.0	3.4	3.2	3.1	3.0	3.4	3.2	3.1	3.0	3.3	3.1	3.0	2.9	2.9
	否	0.56	1.0	3.6	3.4	3.3	3.2	3.6	3.4	3.3	3.2	3.5	3.4	3.2	3.2	3.4	3.3	3.2	3.1	3.1
			1.25	3.7	3.6	3.4	3.3	3.7	3.5	3.4	3.3	3.6	3.5	3.4	3.3	3.6	3.4	3.4	3.3	3.2
下方投影面積			1.5	3.8	3.7	3.5	3.5	3.8	3.6	3.5	3.4	3.7	3.6	3.5	3.4	3.6	3.5	3.5	3.4	3.3
			2.0	3.9	3.8	3.7	3.6	3.9	3.8	3.7	3.6	3.8	3.7	3.6	3.6	3.7	3.6	3.6	3.5	3.5
取付高さ	器具間隔最大限		2.5	4.0	3.9	3.8	3.7	3.9	3.8	3.8	3.7	3.8	3.8	3.7	3.6	3.8	3.7	3.7	3.6	3.5
	横方向 (A)	縦方向 (B)	3.0	4.0	3.9	3.8	3.8	4.0	3.9	3.8	3.8	3.9	3.8	3.8	3.7	3.8	3.8	3.7	3.7	3.6
Hm	0.87Hm	0.86Hm	4.0	4.1	4.0	3.9	3.9	4.0	3.9	3.9	3.8	3.9	3.9	3.8	3.8	3.9	3.8	3.8	3.7	3.7
			5.0	4.1	4.0	4.0	3.9	4.0	4.0	3.9	3.9	4.0	3.9	3.9	3.8	3.9	3.8	3.8	3.8	3.7
			7.0	4.1	4.1	4.0	4.0	4.1	4.0	4.0	4.0	4.0	4.0	3.9	3.9	3.9	3.9	3.9	3.8	3.7
			10.0	4.1	4.1	4.1	4.1	4.1	4.1	4.0	4.0	4.0	4.0	4.0	4.0	3.9	3.9	3.9	3.9	3.8

