

屋内照明器具特性

品番 (品名)	SLB15782+SLK22009+SLK290														
光源	LLD3421LCB1 ×1 700.0 1 m														
管理番号	K0193245 (0) DB 1														
BZ分類	BZ2 / 0.9 / BZ3 / 3.5 / BZ4														

器具効率	86 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	14 %	室指数	照明率 (X0.01)																ZCM		
下方光束	72 %																				
保守率	良 中 否 0.63 0.6 0.56	0.6	5.4	4.6	4.0	3.6	5.3	4.5	4.0	3.6	4.9	4.3	3.8	3.5	4.7	4.1	3.7	3.4	3.2		
		0.8	6.1	5.3	4.8	4.4	5.9	5.2	4.7	4.3	5.6	5.0	4.5	4.2	5.2	4.7	4.4	4.1	3.8		
		1.0	6.6	5.9	5.3	4.9	6.4	5.7	5.2	4.8	6.0	5.4	5.0	4.7	5.6	5.2	4.8	4.5	4.2		
		1.25	7.0	6.3	5.8	5.4	6.8	6.2	5.7	5.3	6.4	5.9	5.5	5.1	6.0	5.6	5.2	5.0	4.6		
下方投影面積 等価発光面積	c m ² c m ²	1.5	7.3	6.7	6.2	5.8	7.1	6.5	6.1	5.7	6.6	6.2	5.8	5.5	6.2	5.9	5.5	5.3	4.9		
		2.0	7.7	7.2	6.7	6.4	7.4	7.0	6.6	6.3	7.0	6.6	6.3	6.0	6.5	6.2	6.0	5.8	5.3		
		2.5	7.9	7.5	7.1	6.8	7.7	7.3	6.9	6.6	7.2	6.9	6.6	6.3	6.8	6.5	6.3	6.1	5.6		
取付 高さ	器具間隔最大限		3.0	8.1	7.7	7.3	7.1	7.8	7.5	7.2	6.9	7.3	7.1	6.8	6.6	6.9	6.7	6.5	6.3	5.8	
	横方向 (A)	縦方向 (B)																			
H m	0.63 H m	0.63 H m	4.0	8.3	8.0	7.7	7.4	8.0	7.8	7.5	7.3	7.6	7.3	7.1	6.9	7.1	6.9	6.8	6.6	6.1	
			5.0	8.4	8.2	7.9	7.7	8.2	7.9	7.7	7.5	7.7	7.5	7.3	7.2	7.2	7.1	6.9	6.8	6.3	
			7.0	8.6	8.4	8.2	8.0	8.3	8.1	8.0	7.8	7.8	7.7	7.5	7.4	7.4	7.3	7.1	7.0	6.5	
			10.0	8.7	8.5	8.4	8.3	8.4	8.3	8.2	8.1	7.9	7.8	7.7	7.6	7.5	7.4	7.3	7.2	6.6	

