

屋内照明器具特性	
品番 (品名)	XFL323KL
光源	LDL40S.N/14/26(2600A) ×2 2600.0lm
管理番号	K0126765(1)DR1
BZ分類	BZ3

器具効率	70%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	70%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.77	0.6	4.4	3.6	3.1	2.8	4.3	3.6	3.1	2.8	4.2	3.5	3.1	2.8	4.0	3.4	3.1	2.8	2.6
	中	0.72	0.8	5.1	4.4	3.9	3.5	5.0	4.3	3.9	3.5	4.8	4.2	3.8	3.5	4.7	4.2	3.8	3.5	3.4
	否	0.68	1.0	5.5	4.9	4.4	4.1	5.4	4.8	4.4	4.1	5.2	4.7	4.3	4.0	5.1	4.6	4.3	4.0	3.9
			1.25	5.9	5.3	4.9	4.6	5.8	5.3	4.9	4.6	5.6	5.2	4.8	4.5	5.4	5.1	4.7	4.5	4.3
下方投影面積		cm ²	1.5	6.2	5.7	5.2	4.9	6.1	5.6	5.2	4.9	5.9	5.5	5.1	4.9	5.7	5.3	5.1	4.8	4.7
等価発光面積		cm ²	2.0	6.5	6.1	5.7	5.4	6.4	6.0	5.7	5.4	6.2	5.9	5.6	5.4	6.0	5.8	5.5	5.3	5.1
取付高さ	器具間隔最大限		2.5	6.7	6.4	6.1	5.8	6.6	6.3	6.0	5.8	6.4	6.1	5.9	5.7	6.3	6.0	5.8	5.6	5.5
	横方向 (A)	縦方向 (B)	3.0	6.9	6.6	6.3	6.0	6.8	6.5	6.2	6.0	6.6	6.3	6.1	5.9	6.4	6.2	6.0	5.8	5.7
1.5m	1.76m	1.96m	4.0	7.0	6.8	6.6	6.4	7.0	6.7	6.5	6.3	6.8	6.6	6.4	6.2	6.6	6.4	6.3	6.2	6.0
2	2.33	2.44	5.0	7.2	7.0	6.8	6.6	7.1	6.9	6.7	6.5	6.9	6.7	6.6	6.4	6.7	6.6	6.5	6.3	6.2
2.5	2.9	2.94	7.0	7.3	7.1	7.0	6.9	7.2	7.1	6.9	6.8	7.0	6.9	6.8	6.7	6.8	6.8	6.7	6.6	6.4
3	3.47	3.45	10.0	7.4	7.3	7.2	7.1	7.3	7.2	7.1	7.0	7.1	7.0	7.0	6.9	7.0	6.9	6.8	6.8	6.6

