

# 屋内照明器具特性

|         |                             |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|---------|-----------------------------|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
| 品番 (品名) | XLX450NENT                  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 光源      | LED5000_85_5200 x1 5200.0lm |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| 管理番号    | K0135074(*)DB1              |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
| BZ分類    | BZ5                         |  |  |  |  |  |  |  |  |  |  |  |  |  |  |

|        |                  |         |             |      |      |     |     |      |     |     |     |     |     |     |     |     |     |     |     |     |    |
|--------|------------------|---------|-------------|------|------|-----|-----|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|
| 器具効率   | 100%             | 天井      | 80%         |      |      |     | 70% |      |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |    |
|        |                  |         | 反射率         | 壁    | 70   | 50  | 30  | 10   | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0% |
|        |                  |         |             | 床    | 10%  |     |     |      | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 0% |
| 上方光束   | 4%               | 室指数     | 照明率 (X0.01) |      |      |     |     |      |     |     |     |     |     |     |     |     |     |     | ZCM |     |    |
| 下方光束   | 96%              |         |             |      |      |     |     |      |     |     |     |     |     |     |     |     |     |     |     |     |    |
| 保守率    | 良<br>中<br>否      | 0.83    | 0.6         | 5.6  | 4.4  | 3.6 | 3.0 | 5.4  | 4.3 | 3.6 | 3.0 | 5.2 | 4.2 | 3.5 | 3.0 | 4.9 | 4.0 | 3.4 | 3.0 | 2.7 |    |
|        |                  | 0.81    | 0.8         | 6.6  | 5.4  | 4.6 | 4.1 | 6.4  | 5.3 | 4.6 | 4.0 | 6.1 | 5.1 | 4.5 | 4.0 | 5.8 | 5.0 | 4.4 | 3.9 | 3.7 |    |
|        |                  | 0.77    | 1.0         | 7.2  | 6.1  | 5.4 | 4.8 | 7.0  | 6.0 | 5.3 | 4.7 | 6.7 | 5.8 | 5.2 | 4.7 | 6.4 | 5.6 | 5.1 | 4.6 | 4.3 |    |
|        |                  |         | 1.25        | 7.8  | 6.8  | 6.1 | 5.5 | 7.6  | 6.7 | 6.0 | 5.5 | 7.2 | 6.5 | 5.9 | 5.4 | 6.9 | 6.2 | 5.7 | 5.3 | 5.0 |    |
| 下方投影面積 | c m <sup>2</sup> | 1.5     | 8.2         | 7.3  | 6.6  | 6.0 | 8.0 | 7.2  | 6.5 | 6.0 | 7.6 | 6.9 | 6.4 | 5.9 | 7.3 | 6.7 | 6.2 | 5.8 | 5.5 |     |    |
|        |                  | 2.0     | 8.8         | 8.0  | 7.4  | 6.9 | 8.6 | 7.9  | 7.3 | 6.8 | 8.2 | 7.6 | 7.1 | 6.7 | 7.8 | 7.3 | 6.9 | 6.5 | 6.2 |     |    |
| 取付高さ   | 器具間隔最大限          |         | 2.5         | 9.1  | 8.5  | 7.9 | 7.4 | 8.9  | 8.3 | 7.8 | 7.3 | 8.5 | 8.0 | 7.6 | 7.2 | 8.2 | 7.7 | 7.4 | 7.0 | 6.7 |    |
|        | 横方向 (A)          | 縦方向 (B) | 3.0         | 9.4  | 8.8  | 8.3 | 7.8 | 9.2  | 8.6 | 8.2 | 7.8 | 8.8 | 8.3 | 7.9 | 7.6 | 8.4 | 8.1 | 7.7 | 7.4 | 7.1 |    |
| 1.5m   | 1.94m            | 2.1m    | 4.0         | 9.7  | 9.2  | 8.8 | 8.4 | 9.5  | 9.0 | 8.7 | 8.3 | 9.1 | 8.7 | 8.4 | 8.1 | 8.8 | 8.5 | 8.2 | 7.9 | 7.6 |    |
| 2      | 2.56             | 2.64    | 5.0         | 9.9  | 9.5  | 9.1 | 8.8 | 9.7  | 9.3 | 9.0 | 8.7 | 9.3 | 9.0 | 8.7 | 8.5 | 9.0 | 8.7 | 8.5 | 8.3 | 7.9 |    |
| 2.5    | 3.19             | 3.21    | 7.0         | 10.1 | 9.8  | 9.5 | 9.3 | 9.9  | 9.6 | 9.4 | 9.1 | 9.6 | 9.3 | 9.1 | 8.9 | 9.2 | 9.0 | 8.8 | 8.7 | 8.3 |    |
| 3      | 3.8              | 3.79    | 10.0        | 10.3 | 10.1 | 9.8 | 9.6 | 10.1 | 9.9 | 9.7 | 9.5 | 9.7 | 9.6 | 9.4 | 9.3 | 9.4 | 9.3 | 9.1 | 9.0 | 8.6 |    |

