

屋内照明器具特性

品番 (品名)	XL X4 5 0 N E W T															
光源	LED4000_85_4920 x1 4920.0 1 m															
管理番号	K0135074 (*) DB 1															
B Z 分類	B Z 5															

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	4 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	96 %		室指数	照明率 (X0.01) Z C M																
保守率	良	0.83	0.6	5.6	4.4	3.6	3.0	5.4	4.3	3.6	3.0	5.2	4.2	3.5	3.0	4.9	4.0	3.4	3.0	2.7
	中	0.81	0.8	6.6	5.4	4.6	4.1	6.4	5.3	4.6	4.0	6.1	5.1	4.5	4.0	5.8	5.0	4.4	3.9	3.7
	否	0.77	1.0	7.2	6.1	5.4	4.8	7.0	6.0	5.3	4.7	6.7	5.8	5.2	4.7	6.4	5.6	5.1	4.6	4.3
			1.25	7.8	6.8	6.1	5.5	7.6	6.7	6.0	5.5	7.2	6.5	5.9	5.4	6.9	6.2	5.7	5.3	5.0
下方投影面積			1.5	8.2	7.3	6.6	6.0	8.0	7.2	6.5	6.0	7.6	6.9	6.4	5.9	7.3	6.7	6.2	5.8	5.5
等価発光面積			2.0	8.8	8.0	7.4	6.9	8.6	7.9	7.3	6.8	8.2	7.6	7.1	6.7	7.8	7.3	6.9	6.5	6.2
取付高さ	器具間隔最大限		2.5	9.1	8.5	7.9	7.4	8.9	8.3	7.8	7.3	8.5	8.0	7.6	7.2	8.2	7.7	7.4	7.0	6.7
	横方向 (A)	縦方向 (B)	3.0	9.4	8.8	8.3	7.8	9.2	8.6	8.2	7.8	8.8	8.3	7.9	7.6	8.4	8.1	7.7	7.4	7.1
1.5m	1.94 m	2.1 m	4.0	9.7	9.2	8.8	8.4	9.5	9.0	8.7	8.3	9.1	8.7	8.4	8.1	8.8	8.5	8.2	7.9	7.6
2	2.56	2.64	5.0	9.9	9.5	9.1	8.8	9.7	9.3	9.0	8.7	9.3	9.0	8.7	8.5	9.0	8.7	8.5	8.3	7.9
2.5	3.19	3.21	7.0	10.1	9.8	9.5	9.3	9.9	9.6	9.4	9.1	9.6	9.3	9.1	8.9	9.2	9.0	8.8	8.7	8.3
3	3.8	3.79	10.0	10.3	10.1	9.8	9.6	10.1	9.9	9.7	9.5	9.7	9.6	9.4	9.3	9.4	9.3	9.1	9.0	8.6

