

屋内照明器具特性

| | | |
|---------|-----------------------------|----------|
| 品番 (品名) | SLB15782+SLK22011+SLK290 | |
| 光源 | LLD2411LCB1 ×1 | 500.0 lm |
| 管理番号 | K0193688(0)DB1 | |
| BZ分類 | BZ1/0.9/BZ2/2.3/BZ3/8.5/BZ4 | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|------------------|----------|------------------|-----|----|----|-----|-----|----|----|-----|-----|----|----|-----|-----|----|----|----|-----|
| 器具効率 | 92% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | 上方光束 9% | | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 下方光束 | 83% | 床 | | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.63 | 0.6 | 65 | 57 | 52 | 49 | 64 | 57 | 52 | 48 | 61 | 55 | 51 | 48 | 59 | 54 | 50 | 47 | 45 |
| | 中 | 0.6 | 0.8 | 71 | 64 | 59 | 55 | 70 | 63 | 58 | 55 | 67 | 61 | 57 | 54 | 64 | 59 | 56 | 53 | 50 |
| | 否 | 0.56 | 1.0 | 75 | 68 | 63 | 60 | 74 | 67 | 63 | 59 | 70 | 65 | 61 | 58 | 67 | 63 | 59 | 57 | 54 |
| | | | 1.25 | 79 | 73 | 68 | 64 | 77 | 71 | 67 | 63 | 74 | 69 | 65 | 62 | 70 | 66 | 63 | 61 | 58 |
| 下方投影面積 | c m ² | | 1.5 | 82 | 76 | 71 | 68 | 80 | 74 | 70 | 67 | 76 | 72 | 68 | 65 | 73 | 69 | 66 | 63 | 60 |
| | 等価発光面積 | | c m ² | 2.0 | 85 | 80 | 76 | 73 | 83 | 79 | 75 | 72 | 79 | 75 | 72 | 70 | 76 | 72 | 70 | 68 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 87 | 83 | 79 | 76 | 85 | 81 | 78 | 75 | 81 | 78 | 75 | 73 | 77 | 75 | 72 | 70 | 66 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 89 | 85 | 82 | 79 | 87 | 83 | 80 | 78 | 83 | 80 | 77 | 75 | 79 | 77 | 74 | 73 | 68 |
| H m | 0.82 H m | 0.86 H m | 4.0 | 91 | 88 | 85 | 82 | 89 | 86 | 83 | 81 | 85 | 82 | 80 | 78 | 81 | 79 | 77 | 76 | 71 |
| | | | 5.0 | 92 | 89 | 87 | 85 | 90 | 88 | 85 | 83 | 86 | 84 | 82 | 80 | 82 | 80 | 79 | 77 | 73 |
| | | | 7.0 | 94 | 92 | 90 | 88 | 91 | 90 | 88 | 86 | 87 | 86 | 84 | 83 | 83 | 82 | 81 | 80 | 75 |
| | | | 10.0 | 95 | 93 | 92 | 90 | 93 | 91 | 90 | 89 | 88 | 87 | 86 | 85 | 84 | 84 | 83 | 82 | 77 |

