

屋内照明器具特性

品番 (品名)	XND1052SW	
光源	LED4000_85_1030 ×1	1030.0 lm
管理番号	K0158888(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床	10%				10%				10%				10%				0%	
室指数			照明率 (X0.01)																ZCM	
保守率	良	0.81	0.6	91	87	84	82	91	86	84	82	90	86	83	82	89	85	83	82	81
	中	0.77	0.8	95	92	89	87	95	91	89	87	94	90	88	87	93	90	88	86	85
	否	0.68	1.0	98	95	92	90	97	94	92	90	96	93	91	90	95	93	91	89	88
下方投影面積 等価発光面積	cm ²	1.25	1.00	97	95	93	99	97	95	93	98	96	94	92	97	95	93	92	91	
		1.5	1.02	99	97	95	101	98	96	95	99	97	95	94	98	96	95	93	92	
		2.0	1.03	101	99	98	102	100	99	97	101	99	98	96	99	98	97	96	94	
取付高さ	器具間隔最大限		2.5	1.04	1.03	1.01	1.00	1.03	1.02	1.00	99	1.02	1.00	99	98	1.00	99	98	97	95
	横方向 (A)	縦方向 (B)	3.0	1.05	1.03	1.02	1.01	1.04	1.03	1.01	1.00	1.02	1.01	1.00	99	1.00	99	99	98	96
Hm	0.75Hm	0.75Hm	4.0	1.06	1.05	1.03	1.02	1.05	1.04	1.03	1.02	1.03	1.02	1.01	1.00	1.01	1.00	1.00	99	97
			5.0	1.06	1.05	1.04	1.04	1.05	1.04	1.04	1.03	1.03	1.03	1.02	1.01	1.02	1.01	1.00	1.00	97
			7.0	1.07	1.06	1.06	1.05	1.06	1.05	1.05	1.04	1.04	1.03	1.03	1.02	1.02	1.01	1.01	1.01	98
			10.0	1.08	1.07	1.06	1.06	1.06	1.06	1.05	1.05	1.04	1.04	1.03	1.03	1.02	1.02	1.02	1.01	99

