

屋内照明器具特性

品番 (品名)	XND1060SN	
光源	LED5000_85_1060 ×1	1060.0 lm
管理番号	K0158886(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	壁	照明率 (X0.01)																ZCM	
下方光束	100%	床	照明率 (X0.01)																ZCM	
保守率	良 中 否	0.81 0.77 0.68	室指数																	
						0.6	86	81	77	75	86	80	77	75	84	80	77	74	83	79
			0.8	92	87	83	81	91	86	83	81	89	85	83	80	88	85	82	80	79
			1.0	95	91	87	85	94	90	87	85	93	89	87	84	91	88	86	84	83
			1.25	98	94	91	89	97	93	91	88	95	92	90	88	94	91	89	87	86
			1.5	100	96	93	91	99	95	93	91	97	94	92	90	95	93	91	90	88
			2.0	102	99	97	95	101	98	96	94	99	97	95	93	97	95	94	93	91
			2.5	103	101	99	97	102	100	98	97	100	98	97	96	98	97	96	95	93
			3.0	104	102	100	99	103	101	100	98	101	100	98	97	99	98	97	96	94
			4.0	105	104	102	101	104	103	101	100	102	101	100	99	100	99	98	97	95
			5.0	106	105	103	102	105	104	103	102	103	102	101	100	101	100	99	99	96
			7.0	107	106	105	104	106	105	104	103	103	103	102	101	101	101	100	100	97
			10.0	107	107	106	105	106	105	104	104	103	103	102	102	101	101	101	101	98

