

屋内照明器具特性

品番 (品名)	XLX467BHWT_55DEG									
光源	LED4000_85_5630 x1 5630.0lm									
管理番号	K0145761(*)DB1									
BZ分類	BZ5/1.4/BZ4									

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	床	10%				10%				10%				10%				0%
下方光束	100%		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否	0.81	0.6	56	44	36	31	55	44	36	31	53	42	36	31	51	41	35	30	29
		0.77	0.8	67	55	48	42	65	55	47	42	63	53	47	42	60	52	46	41	39
			1.0	74	63	56	50	72	62	55	50	69	61	54	49	67	59	54	49	47
		0.68	1.25	80	70	63	58	78	70	63	58	75	68	62	57	73	66	61	57	54
下方投影面積	c m ²	1.5	84	76	69	64	83	75	68	63	80	73	67	63	77	71	66	62	60	
		2.0	90	83	77	72	88	82	76	72	85	80	75	71	83	78	74	70	68	
取付高さ	器具間隔最大限		2.5	93	87	82	78	92	86	82	78	89	84	80	77	86	82	79	76	73
	横方向 (A)	縦方向 (B)	3.0	96	91	86	82	94	90	85	82	91	87	84	81	89	85	82	80	77
1.5m	1.96m	2.17m	4.0	99	95	91	88	97	94	90	87	95	91	89	86	92	89	87	85	82
2	2.59	2.74	5.0	101	97	94	92	99	96	93	91	97	94	92	89	94	92	90	88	85
2.5	3.22	3.33	7.0	103	100	98	96	101	99	97	95	99	97	95	93	96	95	93	92	89
3	3.85	3.94	10.0	104	103	101	99	103	101	100	98	101	99	98	97	98	97	96	95	92

