

屋内照明器具特性

品番 (品名)	XND1534WE														
光源	LED3000_85_1155 x1 1155.0lm														
管理番号	K0163463(0)DB1														
BZ分類	BZ2/8.5/BZ1														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	床	10%				10%				10%				10%				0%
下方光束	100%		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否	0.81	0.6	70	61	55	51	69	60	55	51	67	59	54	50	65	58	54	50	49
		0.77	0.8	79	71	65	61	78	71	65	61	76	69	65	61	74	68	64	61	59
		0.68	1.0	85	78	73	69	84	77	72	69	82	76	72	68	80	75	71	68	66
			1.25	90	84	79	75	89	83	78	75	87	81	78	74	84	80	77	74	72
下方投影面積	c m ²	1.5	93	87	83	79	92	87	82	79	90	85	81	79	87	84	81	78	76	
		2.0	97	92	89	86	96	92	88	85	93	90	87	84	91	88	86	83	81	
取付高さ	器具間隔最大限		2.5	99	96	92	90	98	95	92	89	96	93	90	88	94	91	89	87	
	横方向 (A)	縦方向 (B)	3.0	101	98	95	92	100	97	94	92	97	95	93	91	95	93	91	89	
H m	1.14 H m	1.20 H m	4.0	103	100	98	96	102	99	97	95	99	97	96	94	97	95	94	93	
			5.0	104	102	100	98	103	101	99	97	100	99	97	96	98	97	96	95	92
			7.0	105	104	102	101	104	103	101	100	102	101	99	98	100	99	98	94	
			10.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	96	

