

屋内照明器具特性

品番 (品名)	SLB15783 + SLK22008	
光源	LLD3411LCB1 ×1	700.0 1m
管理番号	K0192996 (0) DB 1	
BZ分類	BZ1	

器具効率	98%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	98%	床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.67	0.6	88	83	81	79	87	83	80	78	86	83	80	78	85	82	80	78	77
	中	0.63	0.8	93	88	86	84	92	88	86	84	91	87	85	83	89	87	85	83	82
	否	0.56	1.0	95	92	89	87	95	91	89	87	93	90	88	87	92	90	88	86	85
下方投影面積	等価発光面積	cm ²	1.25	97	94	92	90	97	94	92	90	95	93	91	89	94	92	90	89	88
			1.5	99	96	94	92	98	95	93	92	96	94	93	91	95	93	92	91	89
取付高さ	器具間隔最大限		2.5	102	100	98	97	101	99	98	96	99	98	96	95	97	96	95	94	93
	横方向 (A)	縦方向 (B)	3.0	103	101	99	98	102	100	99	98	100	98	97	96	98	97	96	95	93
Hm	0.76Hm	0.76Hm	4.0	103	102	101	100	102	101	100	99	100	100	99	98	99	98	97	97	94
			5.0	104	103	102	101	103	102	101	100	101	100	99	99	99	98	98	97	95
			7.0	105	104	103	102	104	103	102	101	102	101	100	100	100	99	99	98	96
			10.0	105	105	104	104	104	104	103	103	102	102	101	101	100	100	99	99	96

