

# 屋内照明器具特性

|         |                     |          |
|---------|---------------------|----------|
| 品番 (品名) | XND2000WW           |          |
| 光源      | LED4000_85_2005 ×1  | 2005.0lm |
| 管理番号    | K0158867(0)DB1      |          |
| BZ分類    | BZ1/4.5/BZ2/6.0/BZ1 |          |

|                  |                 |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |     |
|------------------|-----------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|-----|
| 器具効率             | 100%            | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |    |    | 0% |     |
|                  | 上方光束<br>0%      |         | 壁    | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50 | 30 | 10 | 0%  |
| 下方光束             | 100%            | 床       |      | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |    |    |    | 0%  |
| 室指数              | 照明率 (X0.01)     |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    | ZCM |
| 保守率              | 良 0.81          | 0.6     | 73   | 65  | 59  | 56  | 72  | 64  | 59  | 56  | 71  | 64  | 59  | 55  | 69  | 63  | 58 | 55 | 54 |     |
|                  | 中 0.77          |         | 0.8  | 82  | 74  | 69  | 65  | 81  | 74  | 69  | 65  | 79  | 73  | 68  | 65  | 77  | 72 | 68 | 65 | 63  |
|                  | 否 0.68          |         | 1.0  | 87  | 80  | 75  | 72  | 86  | 79  | 75  | 71  | 84  | 78  | 74  | 71  | 82  | 77 | 74 | 71 | 69  |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup> | 1.25    | 91   | 85  | 81  | 77  | 90  | 85  | 80  | 77  | 88  | 83  | 79  | 76  | 86  | 82  | 79 | 76 | 74 |     |
|                  |                 | 1.5     | 94   | 89  | 85  | 81  | 93  | 88  | 84  | 81  | 91  | 87  | 83  | 80  | 89  | 85  | 82 | 80 | 78 |     |
| 取付高さ             | 器具間隔最大限         |         | 2.5  | 100 | 96  | 93  | 91  | 99  | 95  | 93  | 90  | 96  | 94  | 91  | 89  | 94  | 92 | 90 | 88 | 86  |
|                  | 横方向 (A)         | 縦方向 (B) | 3.0  | 101 | 98  | 96  | 93  | 100 | 97  | 95  | 93  | 98  | 95  | 93  | 91  | 96  | 94 | 92 | 90 | 88  |
| Hm               | 0.74Hm          | 0.74Hm  | 4.0  | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 100 | 98  | 96  | 95  | 98  | 96 | 95 | 93 | 91  |
|                  |                 |         | 5.0  | 104 | 102 | 100 | 99  | 103 | 101 | 100 | 98  | 101 | 99  | 98  | 97  | 99  | 97 | 96 | 95 | 93  |
|                  |                 |         | 7.0  | 105 | 104 | 103 | 101 | 104 | 103 | 102 | 100 | 102 | 101 | 100 | 99  | 100 | 99 | 98 | 97 | 95  |
|                  |                 |         | 10.0 | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 101 | 100 | 99 | 99 | 96 | 96  |

