

屋内照明器具特性

品番 (品名)	SLB15783 + SLK22010 + SLK290		
光源	LLD3421LCB1 ×1	700.0 1m	
管理番号	K0193685 (0) DB1		
BZ分類	BZ1 / 1.8 / BZ2 / 8.5 / BZ3		

器具効率	97 %	天井	80 %				70 %				50 %				30 %				0 %		
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10			
上方光束	11 %	反射率	壁	10 %				10 %				10 %				10 %				0 %	
下方光束	86 %		床	10 %				10 %				10 %				10 %				0 %	
		室指数	照明率 (X0.01)																ZCM		
保守率	良 0.63	0.6	0.6	70	62	57	54	69	61	57	53	66	60	56	53	64	58	55	52	50	
	中 0.6	0.6	0.8	77	69	65	61	75	68	64	60	72	66	62	59	69	64	61	58	56	
	否 0.56	1.0	81	74	70	66	79	73	69	65	76	71	67	64	73	68	65	63	60		
下方投影面積	c m ²	1.25	85	79	74	71	83	77	73	70	79	75	71	68	76	72	69	67	63		
		1.5	87	82	77	74	85	80	76	73	81	77	74	71	78	74	72	69	66		
等価発光面積	c m ²	2.0	91	86	82	79	89	84	81	78	84	81	78	76	81	78	75	73	70		
		2.5	93	89	85	82	91	87	84	81	86	83	81	79	82	80	78	76	72		
取付高さ	器具間隔最大限		3.0	94	91	88	85	92	89	86	84	88	85	83	81	84	82	80	78	74	
H m	0.54 H m	縦方向 (B)	0.54 H m	4.0	96	93	91	88	94	91	89	87	89	87	85	84	85	84	82	81	76
				5.0	97	95	93	91	95	93	91	89	91	89	87	86	86	85	84	83	78
				7.0	99	97	95	94	96	95	93	92	92	91	89	88	87	86	85	79	
				10.0	100	98	97	96	97	96	95	94	93	92	91	90	89	88	87	81	

