

# 屋内照明器具特性

品番 (品名)	SLB15783+SLK22011+SLK290	
光源	LLD3401LCB1 ×1                      700.0 1 m	
管理番号	K0193689 ( 0 ) DB 1	
BZ分類	BZ4/4.5/BZ5	

器具効率	87 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 12 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	75 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 ( X0.01 )																			ZCM
保守率	良	0.63	0.6	5.2	4.2	3.6	3.2	5.0	4.1	3.5	3.1	4.7	3.9	3.4	3.0	4.4	3.8	3.3	3.0	2.7
	中	0.6	0.8	6.0	5.1	4.4	4.0	5.8	4.9	4.4	3.9	5.4	4.7	4.2	3.8	5.1	4.5	4.1	3.7	3.5
	否	0.56	1.0	6.5	5.6	5.0	4.6	6.3	5.5	5.0	4.5	5.9	5.3	4.8	4.4	5.5	5.0	4.6	4.3	4.0
			1.25	6.9	6.2	5.6	5.2	6.7	6.0	5.5	5.1	6.3	5.7	5.3	4.9	5.9	5.5	5.1	4.8	4.4
下方投影面積	c m <sup>2</sup>		1.5	7.3	6.6	6.0	5.6	7.0	6.4	5.9	5.5	6.6	6.1	5.7	5.3	6.2	5.8	5.4	5.1	4.8
等価発光面積	c m <sup>2</sup>		2.0	7.7	7.1	6.6	6.2	7.4	6.9	6.5	6.1	7.0	6.6	6.2	5.9	6.6	6.2	5.9	5.7	5.3
取付高さ	器具間隔最大限		2.5	7.9	7.4	7.0	6.6	7.7	7.2	6.9	6.5	7.3	6.9	6.6	6.3	6.8	6.5	6.3	6.0	5.6
	横方向 (A)	縦方向 (B)	3.0	8.1	7.7	7.3	7.0	7.9	7.5	7.1	6.8	7.4	7.1	6.8	6.5	7.0	6.7	6.5	6.3	5.8
H m	1.01H m	1.01H m	4.0	8.4	8.0	7.7	7.4	8.1	7.8	7.5	7.2	7.7	7.4	7.2	6.9	7.2	7.0	6.8	6.6	6.2
			5.0	8.5	8.2	7.9	7.7	8.3	8.0	7.7	7.5	7.8	7.6	7.4	7.2	7.4	7.2	7.0	6.9	6.4
			7.0	8.7	8.5	8.2	8.0	8.4	8.2	8.0	7.9	8.0	7.8	7.7	7.5	7.6	7.4	7.3	7.2	6.6
			10.0	8.8	8.6	8.5	8.3	8.6	8.4	8.3	8.1	8.1	8.0	7.9	7.8	7.7	7.6	7.5	7.4	6.9

