

屋内照明器具特性

品番 (品名)	SLB15783+SLK22011+SLK290									
光源	LLD3411LCB1 ×1 700.0 1 m									
管理番号	K0193690 (0) DB 1									
BZ分類	BZ1 / 0.9 / BZ2 / 1.8 / BZ3 / 6.0 / BZ4									

器具効率	92 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		10 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		82 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	c m ²		1.25	78	72	67	63	76	70	66	62	73	68	64	61	69	65	62	60	56	
	等価発光面積	c m ²		1.5	81	75	70	67	79	73	69	66	75	71	67	64	72	68	65	62	59
取付高さ		器具間隔最大限		2.5	86	82	78	75	84	80	77	74	80	77	74	72	76	74	71	69	65
	H m	横方向 (A)	縦方向 (B)	3.0	88	84	81	78	86	82	79	77	82	79	76	74	78	76	73	72	67
H m		0.82 H m	0.87 H m	4.0	90	87	84	82	88	85	82	80	84	81	79	77	80	78	76	75	70
	H m			5.0	91	89	86	84	89	87	84	82	85	83	81	79	81	79	78	76	72
H m				7.0	93	91	89	87	91	89	87	85	86	85	83	82	82	81	80	79	74
	H m			10.0	94	92	91	90	92	90	89	88	87	86	85	84	83	83	82	81	76

