

屋内照明器具特性	
品番 (品名)	XND2065SL
光源	LED3000_85_1905 ×1 1905.0lm
管理番号	K0163457 (0) DB1
BZ分類	BZ2/0.7/BZ1

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
				室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 8 1	0 . 6	7 1	6 1	5 6	5 2	7 0	6 1	5 5	5 1	6 8	6 0	5 5	5 1	6 6	5 9	5 5	5 1	5 0				
			0 . 7 7	0 . 8	8 0	7 3	6 7	6 3	7 9	7 2	6 7	6 3	7 7	7 1	6 6	6 3	7 6	7 0	6 6	6 3	6 1				
			1 . 0	1 . 0	8 6	8 0	7 5	7 1	8 5	7 9	7 4	7 1	8 3	7 8	7 3	7 0	8 1	7 7	7 3	7 0	6 8				
			0 . 6 8	1 . 2 5	9 1	8 5	8 1	7 7	9 0	8 4	8 0	7 7	8 8	8 3	7 9	7 6	8 6	8 2	7 9	7 6	7 4				
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	1 . 5	9 4	8 9	8 5	8 1	9 3	8 8	8 4	8 1	9 1	8 7	8 3	8 0	8 9	8 5	8 2	8 0	7 8				
			2 . 0	2 . 0	9 8	9 4	9 0	8 7	9 7	9 3	9 0	8 7	9 4	9 1	8 8	8 6	9 2	9 0	8 7	8 5	8 3				
			2 . 5	2 . 5	1 0 0	9 7	9 4	9 1	9 9	9 6	9 3	9 0	9 7	9 4	9 2	8 9	9 5	9 2	9 0	8 8	8 6				
取付 高さ	器具間隔最大限		3 . 0	3 . 0	1 0 2	9 8	9 6	9 4	1 0 0	9 8	9 5	9 3	9 8	9 6	9 4	9 2	9 6	9 4	9 2	9 1	8 9				
	横方向 (A)	縦方向 (B)	4 . 0	4 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 5	9 8	9 6	9 5	9 4	9 1				
H m	1 . 3 3 H m	1 . 3 3 H m	5 . 0	5 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	9 9	9 8	9 7	9 9	9 8	9 6	9 5	9 3				
			7 . 0	7 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 5				
			1 0 . 0	1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 4	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 6				

