

屋内照明器具特性

| | | |
|---------|--------------------|----------|
| 品番 (品名) | XND2064WN | |
| 光源 | LED5000_85_2045 x1 | 2045.0lm |
| 管理番号 | K0163462(2)DB1 | |
| BZ分類 | BZ2/0.7/BZ1 | |

| | | | | | | | | | | | | | | | | | | | | | |
|--------|-----------------|---------|--------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|-----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | |
| | 上方光束 0% | | 下方光束 100% | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.81 | 0.6 | 71 | 61 | 56 | 52 | 70 | 61 | 55 | 51 | 68 | 60 | 55 | 51 | 66 | 59 | 55 | 51 | 50 | |
| | 中 | 0.77 | 0.8 | 80 | 72 | 67 | 63 | 79 | 72 | 67 | 63 | 77 | 71 | 66 | 63 | 75 | 70 | 66 | 62 | 61 | |
| | 否 | 0.68 | 1.0 | 86 | 79 | 74 | 71 | 85 | 79 | 74 | 70 | 83 | 77 | 73 | 70 | 81 | 76 | 73 | 70 | 68 | |
| | | | 1.25 | 91 | 85 | 80 | 77 | 90 | 84 | 80 | 77 | 88 | 83 | 79 | 76 | 86 | 82 | 78 | 76 | 74 | |
| 下方投影面積 | cm ² | | 1.5 | 94 | 89 | 84 | 81 | 93 | 88 | 84 | 81 | 91 | 86 | 83 | 80 | 89 | 85 | 82 | 80 | 78 | |
| 等価発光面積 | cm ² | | 2.0 | 98 | 93 | 90 | 87 | 97 | 93 | 89 | 87 | 94 | 91 | 88 | 86 | 92 | 89 | 87 | 85 | 83 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 100 | 96 | 93 | 91 | 99 | 95 | 93 | 90 | 97 | 94 | 91 | 89 | 94 | 92 | 90 | 88 | 86 | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 101 | 98 | 96 | 93 | 100 | 97 | 95 | 93 | 98 | 96 | 93 | 92 | 96 | 94 | 92 | 91 | 88 | |
| Hm | 1.31Hm | 1.32Hm | 4.0 | 103 | 101 | 99 | 97 | 102 | 100 | 98 | 96 | 100 | 98 | 96 | 95 | 98 | 96 | 95 | 93 | 91 | |
| | | | 5.0 | 104 | 102 | 101 | 99 | 103 | 101 | 100 | 98 | 101 | 99 | 98 | 97 | 99 | 97 | 96 | 95 | 93 | |
| | | | 7.0 | 106 | 104 | 103 | 102 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99 | 100 | 99 | 98 | 97 | 95 | |
| | | | 10.0 | 106 | 105 | 104 | 104 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 100 | 100 | 99 | 99 | 96 | |

