

# 屋内照明器具特性

品番 (品名)	XLX450DENT														
光源	LED5000_85_5200 x1 5200.0lm														
管理番号	K0130919(*)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	4%																				
下方光束	96%																				
		室指数	照明率 (X0.01) ZCM																		
保守率	良 0.83 中 0.81 否 0.77	0.6	55	42	34	29	53	42	34	29	51	40	33	28	48	39	33	28	26		
		0.8	65	53	45	39	63	52	44	38	60	50	43	38	57	48	42	37	35		
		1.0	71	60	52	46	69	59	51	46	66	57	50	45	62	55	49	44	42		
		1.25	77	67	59	53	75	66	58	53	71	63	57	52	68	61	56	51	48		
下方投影面積	c m <sup>2</sup>	1.5	81	72	65	59	79	70	64	58	75	68	62	57	72	66	60	56	53		
		2.0	87	79	72	67	85	77	71	66	81	75	69	65	77	72	68	64	60		
		2.5	90	84	78	73	88	82	77	72	85	79	74	70	81	76	72	69	66		
取付高さ	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
1.5m	1.99m	2.17m	4.0	96	91	87	83	94	90	86	82	91	87	83	80	87	84	81	78	75	
2	2.62	2.74	5.0	98	94	90	87	96	93	89	86	93	89	86	84	89	87	84	82	78	
2.5	3.26	3.32	7.0	101	97	95	92	99	96	93	91	95	93	90	88	92	90	88	86	82	
3	3.89	3.92	10.0	102	100	98	96	101	99	96	95	97	95	94	92	94	92	91	90	86	

