

屋内照明器具特性	
品番 (品名)	XLX467BHWT_65DEG
光源	LED4000_85_5630 ×1 5630.0lm
管理番号	K0145763 (＊)DB1
BZ分類	BZ5/0.7/BZ4

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 ( X0.01 )																ZCM
保守率		良 中 否	0.81	0.6	58	46	38	33	57	45	38	33	54	44	38	33	52	43	37	33	31
			0.77	0.8	68	57	49	44	67	56	49	44	64	55	48	43	61	54	48	43	41
			0.68	1.0	75	64	57	51	73	64	57	51	70	62	56	51	68	61	55	51	48
				1.25	81	71	65	59	79	71	64	59	76	69	63	58	74	67	62	58	56
下方投影面積		cm <sup>2</sup>		1.5	85	76	70	65	83	76	69	64	80	74	68	64	78	72	67	63	61
			等価発光面積		cm <sup>2</sup>	2.0	90	83	78	73	89	82	77	73	86	80	76	72	83	78	75
取付 高さ	器具間隔最大限		2.5	94	88	83	79	92	87	82	78	89	85	81	77	87	83	79	76	74	
	横方向 ( A )	縦方向 ( B )	3.0	96	91	87	83	95	90	86	82	92	88	84	81	89	86	83	80	78	
1.5m	1.65 m	2.15 m	4.0	99	95	91	88	98	94	91	88	95	92	89	86	92	90	87	85	82	
2	2.18	2.71	5.0	101	98	95	92	99	96	94	91	97	94	92	90	94	92	90	88	86	
2.5	2.72	3.3	7.0	103	100	98	96	101	99	97	95	99	97	95	94	96	95	93	92	89	
3	3.25	3.9	10.0	104	103	101	99	103	101	100	98	101	99	98	97	98	97	96	95	92	

