

屋内照明器具特性

品番 (品名)	XND2552SL	
光源	LED3000_85_2305 ×1	2305.0 lm
管理番号	K0158888(0)DB1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	100%	床		10%				10%				10%				10%				0%	
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.81	0.6	91	87	84	82	91	86	84	82	90	86	83	82	89	85	83	82	81	
	中	0.77	0.8	95	92	89	87	95	91	89	87	94	90	88	87	93	90	88	86	85	
	否	0.68	1.0	98	95	92	90	97	94	92	90	96	93	91	90	95	93	91	89	88	
下方投影面積 等価発光面積	cm ²	1.25	100	97	95	93	99	97	95	93	98	96	94	92	97	95	93	92	91		
		1.5	102	99	97	95	101	98	96	95	99	97	95	94	98	96	95	93	92		
		2.0	103	101	99	98	102	100	99	97	101	99	98	96	99	98	97	96	94		
取付高さ	器具間隔最大限		2.5	104	103	101	100	103	102	100	99	102	100	99	98	100	99	98	97	95	
	横方向 (A)	縦方向 (B)	3.0	105	103	102	101	104	103	101	100	102	101	100	99	100	99	99	98	96	
Hm	0.75Hm	0.75Hm	4.0	106	105	103	102	105	104	103	102	103	102	101	100	101	100	100	99	97	
			5.0	106	105	104	104	105	104	104	103	103	103	102	101	102	101	100	100	97	
			7.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	101	98	
			10.0	108	107	106	106	106	106	105	105	104	104	103	103	102	102	102	101	99	

