

# 屋内照明器具特性

品番 (品名)	SLB15784 + SLK22002 + SLK290	
光源	LLD2411LCB1 ×1                      500.0 l m	
管理番号	K0192485 (1) DR 1	
BZ分類	BZ1	

器具効率	75 %	天井	80 %				70 %				50 %				30 %				0 %			
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
上方光束	0 %	反射率	床	10 %				10 %				10 %				10 %				0 %		
下方光束	75 %		室指数	照明率 ( X0.01 )																ZCM		
保守率	良	0.67	0.6	63	58	55	53	62	58	55	53	61	58	55	53	60	57	55	53	52		
	中	0.63	0.8	68	64	61	59	67	63	61	59	66	63	60	59	65	62	60	59	58		
	否	0.56	1.0	71	67	64	63	70	67	64	62	69	66	64	62	68	65	63	62	61		
下方投影面積	c m <sup>2</sup>	等価発光面積	c m <sup>2</sup>	1.25	73	70	67	66	72	69	67	66	71	68	67	65	70	68	66	65	64	
				1.5	74	72	70	68	74	71	69	68	72	70	68	67	71	69	68	67	65	
取付高さ	器具間隔最大限		H m	0.70 H m	0.70 H m	2.5	77	75	74	73	76	75	73	72	75	74	72	71	74	72	71	69
	横方向 (A)	縦方向 (B)				3.0	78	76	75	74	77	76	74	73	76	74	73	73	74	73	72	72
H m	0.70 H m	0.70 H m	4.0	79	78	77	76	78	77	76	75	76	76	75	74	75	74	74	73	71		
			5.0	79	78	77	77	79	78	77	76	77	76	76	75	75	75	75	74	74	72	
			7.0	80	79	79	78	79	78	78	77	78	77	77	76	76	76	75	75	73		
			10.0	80	80	79	79	80	79	79	78	78	78	77	77	76	76	76	76	74		

