

# 屋内照明器具特性

|         |                              |           |
|---------|------------------------------|-----------|
| 品番 (品名) | SLB15784 + SLK22003 + SLK290 |           |
| 光源      | LLD2411LCB1 ×1               | 500.0 l m |
| 管理番号    | K0193681 ( 0 ) DB 1          |           |
| BZ分類    | BZ1 / 4.5 / BZ2              |           |

|        |                  |           |                  |          |          |          |          |          |          |          |          |          |          |          |          |          |          |          |          |          |          |
|--------|------------------|-----------|------------------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|----------|
| 器具効率   | 99 %             | 天井        | 80 %             |          |          |          | 70 %     |          |          |          | 50 %     |          |          |          | 30 %     |          |          |          | 0 %      |          |          |
|        | 上方光束<br>7 %      |           | 反射率              | 70       | 50       | 30       | 10       | 70       | 50       | 30       | 10       | 70       | 50       | 30       | 10       | 70       | 50       | 30       | 10       | 0 %      |          |
| 下方光束   | 92 %             | 床         |                  | 10 %     |          |          |          | 10 %     |          |          |          | 10 %     |          |          |          | 10 %     |          |          |          | 0 %      |          |
| 室指数    | 照明率 ( X0.01 )    |           |                  |          |          |          |          |          |          |          |          |          |          |          |          |          |          |          |          |          | ZCM      |
| 保守率    | 良                | 0.63      | 0.6              | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      |
|        | 中                | 0.6       | 0.6              | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      | 0.6      |
|        | 否                | 0.56      | 0.56             | 0.56     | 0.56     | 0.56     | 0.56     | 0.56     | 0.56     | 0.56     | 0.56     | 0.56     | 0.56     | 0.56     | 0.56     | 0.56     | 0.56     | 0.56     | 0.56     | 0.56     | 0.56     |
| 下方投影面積 | c m <sup>2</sup> |           | 1.25             | 1.5      | 2.0      | 2.5      | 3.0      | 4.0      | 5.0      | 7.0      | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     |
|        | 等価発光面積           |           | c m <sup>2</sup> | 1.5      | 2.0      | 2.5      | 3.0      | 4.0      | 5.0      | 7.0      | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     |
| 取付高さ   | 器具間隔最大限          |           | 2.5              | 3.0      | 4.0      | 5.0      | 7.0      | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     | 10.0     |
| H m    | 横方向 ( A )        | 縦方向 ( B ) | 0.74 H m         | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m |
|        | 0.74 H m         | 0.74 H m  | 0.74 H m         | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m | 0.74 H m |

