

屋内照明器具特性

品番 (品名)	SLB15784+SLK22003+SLK290	
光源	LLD2411LCB1 ×1	500.0 lm
管理番号	K0193061(0)DB1	
BZ分類	BZ4/0.7/BZ5/3.5/BZ6	

器具効率	89%	天井	80%				70%				50%				30%				0%												
	上方光束		26%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%										
下方光束	63%	床	10%				10%				10%				10%				0%												
室指数	照明率 (X0.01)																				ZCM										
保守率	良	0.63	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	4.8	3.8	3.2	2.7	4.6	3.7	3.1	2.7	4.1	3.4	2.9	2.5	3.7	3.1	2.7	2.4	2.0
	中	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	5.5	4.6	3.9	3.4	5.3	4.4	3.8	3.3	4.7	4.0	3.5	3.1	4.3	3.7	3.2	2.9	2.5	
	否	0.56	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	6.0	5.1	4.5	4.0	5.7	4.9	4.3	3.8	5.1	4.5	4.0	3.6	4.6	4.1	3.7	3.3	2.8		
	下方投影面積	c m ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	6.5	5.6	5.0	4.5	6.2	5.4	4.8	4.3	5.5	4.9	4.4	4.0	5.0	4.5	4.1	3.7	3.2		
取付高さ	器具間隔最大限		横方向 (A)		縦方向 (B)																										
	H m	0.60 H m	0.60 H m	0.60 H m																											
			2.5	3.0	4.0	5.0	7.0	10.0	7.6	7.0	6.5	6.0	7.2	6.6	6.2	5.8	6.5	6.1	5.7	5.3	5.8	5.5	5.2	4.9	4.2						
			3.0	4.0	5.0	7.0	10.0	7.8	7.2	6.8	6.4	7.4	6.9	6.5	6.1	6.7	6.3	5.9	5.6	6.0	5.7	5.4	5.2	4.4							
			4.0	5.0	7.0	10.0	8.0	7.6	7.2	6.8	7.7	7.3	6.9	6.6	6.9	6.6	6.3	6.1	6.2	6.0	5.8	5.5	4.7								
			5.0	7.0	10.0	8.2	7.8	7.5	7.2	7.8	7.5	7.2	6.9	7.1	6.8	6.6	6.3	6.4	6.2	6.0	5.8	5.5	5.0								
			7.0	10.0	8.4	8.1	7.8	7.6	8.0	7.8	7.5	7.3	7.3	7.1	6.9	6.7	6.6	6.4	6.3	6.1	5.2										
			10.0	8.6	8.3	8.1	7.9	8.2	8.0	7.8	7.6	7.5	7.3	7.1	7.0	6.8	6.6	6.5	6.4	5.5											

