

屋内照明器具特性

品番 (品名)	SLB15784 + SLK22003 + SLK290	
光源	LLD3411LCB1 ×1	700.0 1m
管理番号	K0192482 (1) DR 1	
BZ分類	BZ1	

器具効率	75 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0 %	反射率	壁	10 %				10 %				10 %				10 %				0 %
下方光束	75 %		床	10 %				10 %				10 %				10 %				0 %
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	62	58	55	53	62	58	55	53	61	57	55	53	60	57	54	53	52	
	中 0.63	0.8	67	63	61	59	67	63	60	59	66	62	60	58	65	62	60	58	57	
	否 0.56	1.0	70	67	64	62	69	66	64	62	68	65	63	62	67	65	63	62	61	
下方投影面積	c m ²	1.25	72	69	67	65	72	69	67	65	70	68	66	65	69	67	66	64	63	
		1.5	74	71	69	67	73	71	69	67	72	70	68	67	71	69	67	66	65	
等価発光面積	c m ²	2.0	76	74	72	70	75	73	71	70	74	72	70	69	72	71	70	69	67	
		2.5	77	75	73	72	76	74	73	72	75	73	72	71	73	72	71	70	69	
取付高さ	器具間隔最大限		3.0	77	76	75	73	77	75	74	73	75	74	73	72	74	73	72	71	70
H m	0.71H m	0.71H m	4.0	78	77	76	75	78	76	75	75	76	75	74	74	75	74	73	73	71
			5.0	79	78	77	76	78	77	76	76	76	76	75	75	75	74	74	73	72
			7.0	79	79	78	77	79	78	77	77	77	77	76	76	75	75	74	72	
			10.0	80	79	79	78	79	79	78	78	77	77	77	76	76	75	75	73	

