

# 屋内照明器具特性

品番 (品名)	XND3530SW		
光源	LED4000_80_3975 ×1	3975.0 lm	
管理番号	K0162736(0)DB1		
BZ分類	BZ1		

器具効率	100%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	10%		10%		10%		10%		10%		10%		10%		10%			
下方光束	100%		室指数		照明率 (X0.01)															
保守率	良 0.76	0.6	83	76	72	69	82	76	72	69	80	75	72	69	79	74	71	69	68	
	中 0.72	0.8	89	83	80	77	88	83	79	77	87	82	79	76	85	81	78	76	75	
	否 0.64	1.0	93	88	84	82	92	88	84	82	91	87	84	81	89	86	83	81	80	
下方投影面積	cm <sup>2</sup>	1.25	96	92	89	86	95	91	88	86	94	90	88	85	92	89	87	85	83	
		1.5	98	95	92	89	97	94	91	89	96	93	90	88	94	91	89	87	86	
等価発光面積	cm <sup>2</sup>	2.0	101	98	95	93	100	97	95	93	98	96	94	92	96	94	93	91	89	
		2.5	103	100	98	96	102	99	97	95	100	98	96	94	98	96	95	93	91	
取付高さ	器具間隔最大限		3.0	104	101	99	98	103	100	99	97	101	99	97	96	99	97	96	93	
	横方向 (A)	縦方向 (B)	4.0	105	103	102	100	104	102	101	99	102	100	99	98	100	99	98	94	
Hm	0.76Hm	0.76Hm	5.0	106	104	103	102	105	103	102	101	102	101	100	99	100	100	99	96	
			7.0	107	105	104	104	105	104	104	103	103	102	102	101	101	100	99	97	
			10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	100	98	

