

# 屋内照明器具特性

品番 (品名)	SLB15784+SLK22004+SLK290	
光源	LLD3401LCB1 ×1                      700.0 lm	
管理番号	K0192481(1)DR1	
BZ分類	BZ1	

器具効率	38%	天井	80%				70%				50%				30%				0%																																							
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																							
		床	10%				10%				10%				10%				0%																																							
上方光束	0%	室指数																			照明率 (×0.01)																			ZCM																		
下方光束	38%																																																									
保守率	良 中 否	0.67	0.6	3.1	2.9	2.7	2.6	3.1	2.9	2.7	2.6	3.0	2.8	2.7	2.6	3.0	2.8	2.7	2.6	2.6																																						
		0.63	0.8	3.4	3.2	3.0	2.9	3.4	3.2	3.0	2.9	3.3	3.1	3.0	2.9	3.2	3.1	3.0	2.9	2.8																																						
		0.56	1.0	3.5	3.4	3.2	3.1	3.5	3.3	3.2	3.1	3.4	3.3	3.2	3.1	3.4	3.3	3.2	3.1	3.0																																						
			1.25	3.7	3.5	3.4	3.3	3.6	3.5	3.4	3.3	3.6	3.4	3.3	3.2	3.5	3.4	3.3	3.2	3.2																																						
下方投影面積	c m <sup>2</sup>	1.5	3.7	3.6	3.5	3.4	3.7	3.6	3.5	3.4	3.6	3.5	3.4	3.4	3.6	3.5	3.4	3.3	3.3																																							
		2.0	3.8	3.7	3.6	3.5	3.8	3.7	3.6	3.5	3.7	3.6	3.6	3.5	3.7	3.6	3.5	3.5	3.4																																							
取付高さ	器具間隔最大限		2.5	3.9	3.8	3.7	3.6	3.9	3.8	3.7	3.6	3.8	3.7	3.6	3.7	3.6	3.6	3.5	3.5																																							
	横方向 (A)	縦方向 (B)	3.0	3.9	3.8	3.8	3.7	3.9	3.8	3.7	3.7	3.8	3.8	3.7	3.6	3.7	3.7	3.6	3.5																																							
H <sub>m</sub>	0.87H <sub>m</sub>	0.86H <sub>m</sub>	4.0	4.0	3.9	3.8	3.9	3.9	3.8	3.8	3.9	3.8	3.8	3.7	3.8	3.7	3.7	3.7	3.6																																							
			5.0	4.0	4.0	3.9	3.9	4.0	3.9	3.9	3.8	3.9	3.8	3.8	3.8	3.8	3.8	3.7	3.6																																							
			7.0	4.0	4.0	4.0	3.9	4.0	4.0	3.9	3.9	3.9	3.9	3.9	3.9	3.8	3.8	3.8	3.7																																							
			10.0	4.1	4.0	4.0	4.0	4.0	4.0	4.0	4.0	3.9	3.9	3.9	3.9	3.9	3.8	3.8	3.7																																							

