

# 屋内照明器具特性

|         |                             |           |
|---------|-----------------------------|-----------|
| 品番 (品名) | XND1531WL                   |           |
| 光源      | LED3000_85_1585 ×1          | 1585.0 lm |
| 管理番号    | K0158840(5)DB1              |           |
| BZ分類    | BZ2/0.7/BZ1/4.5/BZ2/6.0/BZ1 |           |

|        |                 |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |     |
|--------|-----------------|---------|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|-----|
| 器具効率   | 100%            | 天井      | 80%  |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |    | 0% |    |     |
|        | 上方光束<br>0%      |         | 反射率  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10 | 0% |     |
| 下方光束   | 100%            | 床       |      | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |    |    | 0% |     |
| 室指数    | 照明率 ( X0.01 )   |         |      |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    | ZCM |
| 保守率    | 良               | 0.81    | 0.6  | 71  | 62  | 56  | 52  | 70  | 61  | 56  | 52  | 68  | 60  | 55  | 52  | 66  | 60  | 55 | 52 | 50 |     |
|        | 中               | 0.77    | 0.8  | 80  | 73  | 67  | 63  | 79  | 72  | 67  | 63  | 77  | 71  | 66  | 63  | 76  | 70  | 66 | 63 | 61 |     |
|        | 否               | 0.68    | 1.0  | 86  | 79  | 74  | 70  | 85  | 79  | 74  | 70  | 83  | 77  | 73  | 70  | 81  | 76  | 73 | 70 | 68 |     |
|        |                 |         | 1.25 | 91  | 85  | 80  | 77  | 90  | 84  | 80  | 76  | 88  | 83  | 79  | 76  | 86  | 81  | 78 | 75 | 74 |     |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5  | 94  | 88  | 84  | 81  | 93  | 88  | 84  | 81  | 90  | 86  | 83  | 80  | 88  | 85  | 82 | 79 | 78 |     |
| 等価発光面積 | cm <sup>2</sup> |         | 2.0  | 98  | 93  | 90  | 87  | 96  | 92  | 89  | 86  | 94  | 91  | 88  | 85  | 92  | 89  | 87 | 85 | 83 |     |
| 取付高さ   | 器具間隔最大限         |         | 2.5  | 100 | 96  | 93  | 91  | 99  | 95  | 92  | 90  | 96  | 94  | 91  | 89  | 94  | 92  | 90 | 88 | 86 |     |
|        | 横方向 (A)         | 縦方向 (B) | 3.0  | 101 | 98  | 95  | 93  | 100 | 97  | 95  | 93  | 98  | 95  | 93  | 91  | 96  | 94  | 92 | 90 | 88 |     |
| Hm     | 1.27Hm          | 1.27Hm  | 4.0  | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 100 | 98  | 96  | 95  | 98  | 96  | 95 | 93 | 91 |     |
|        |                 |         | 5.0  | 104 | 102 | 100 | 99  | 103 | 101 | 100 | 98  | 101 | 99  | 98  | 97  | 99  | 97  | 96 | 95 | 93 |     |
|        |                 |         | 7.0  | 106 | 104 | 103 | 101 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 98 | 97 | 95 |     |
|        |                 |         | 10.0 | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 101 | 100 | 100 | 99 | 99 | 96 |     |

